



LYNNWOOD  
WASHINGTON


# CITY OF LYNNWOOD

## LIFT STATIONS 4 & 8 IMPROVEMENTS

ISSUED FOR BIDDING

APRIL 2019 VOLUME 2 OF 2

PROJECT VICINITY MAP



**MAYOR**  
NICOLA SMITH


**PUBLIC WORKS DIRECTOR**  
WILLIAM A. FRANZ, P.E.

**CITY COUNCIL**  
BENJAMIN GOODWIN  
CHRISTINE FRIZZELL  
GEORGE HURST  
IAN COTTON  
RUTH ROSS  
SHANNON SESSIONS  
SHIRLEY SUTTON


CALL 48 HOURS BEFORE YOU DIG  
ONE CALL 1-800-424-5555 (811)

REPORT ALL SPILLS  
DEPT. OF ECOLOGY 1-800-258-5990

LS4 PROJECT LOCATION MAP



LS8 PROJECT LOCATION MAP



Professional Engineer seals for Richard L. Ballard, Edwin Halim, Brian J. Fessenden, Tom Marshall, and Christopher Michael.

PREPARED BY:  
**RH2**  
ENGINEERING  
40 YEARS  
SINCE 1978



## GENERAL NOTES

- CONTRACTOR SHALL CALL 1-800-424-5555 FOR UTILITY LOCATES 48 HOURS BEFORE CONSTRUCTION. THE CONTRACTOR SHALL HAVE ALL UTILITIES LOCATED BY THE APPROPRIATE UTILITY LOCATING PROFESSIONALS, PRIOR TO AND DURING CONSTRUCTION. THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER AND THE UTILITY COMPANY WHEN A CONFLICT OCCURS OR WHEN A CONFLICT IS ANTICIPATED.
- CONTRACTOR INITIATED CHANGES SHALL BE SUBMITTED IN WRITING TO THE ENGINEER FOR APPROVAL PRIOR TO IMPLEMENTATION OR CONSTRUCTION.
- CONTRACTOR MUST KEEP A COPY OF THE APPROVED PLANS ON-SITE WHENEVER CONSTRUCTION IS IN PROGRESS.
- THE CONTRACTOR SHALL TAKE ALL NECESSARY PRECAUTIONS TO PROTECT THE PUBLIC AND PREVENT NUISANCES. CONTRACTOR SHALL PROVIDE TEMPORARY BRACING FOR THE STRUCTURE AND STRUCTURAL COMPONENTS UNTIL ALL FINAL CONNECTIONS HAVE BEEN COMPLETED IN ACCORDANCE WITH THE PLANS.
- THE CONTRACTOR IS RESPONSIBLE FOR PREPARING COMPLETE AS-CONSTRUCTED (AS BUILT) RECORDS, INCLUDING AS-BUILT SURVEYING.
- CONSTRUCTION OF IMPROVEMENTS SHALL CONFORM TO THE CURRENT EDITION OF THE CITY OF LYNNWOOD ENGINEERING STANDARDS AND THE STANDARD SPECIFICATIONS FOR ROAD, BRIDGE AND MUNICIPAL CONSTRUCTION, 2018 EDITION, AS ISSUED BY THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION AND THE AMERICAN PUBLIC WORKS ASSOCIATION. THESE DOCUMENTS HEREINAFTER REFERRED TO AS THE STANDARD SPECIFICATIONS.
- THE CONTRACTOR IS REQUIRED TO PROVIDE ALL CONSTRUCTION STAKING ON THIS PROJECT. STAKING FOR GRADES AND ALIGNMENT SHALL BE PERFORMED BY AN ENGINEERING OR SURVEYING FIRM LICENSED AND CAPABLE OF PERFORMING SUCH WORK. RIGHT OF WAY AND EASEMENT LIMITS MUST BE CLEARLY IDENTIFIED IN THE FIELD DURING CONSTRUCTION.
- CONTRACTOR SHALL RESTORE MARKERS FOR FRONT PROPERTY CORNERS THAT ARE DISTURBED BY CONSTRUCTION. MARKERS SHALL BE RE-ESTABLISHED BY A PROFESSIONAL LAND SURVEYOR LICENSED IN THE STATE OF WASHINGTON.
- A PRECONSTRUCTION CONFERENCE AND 24-HOUR NOTICE WILL BE REQUIRED PRIOR TO STARTING CONSTRUCTION OR RESTARTING CONSTRUCTION AFTER A PERIOD OF MORE THAN 5 DAYS OF NO WORK BEING PERFORMED.
- CONTRACTOR SHALL RESTORE ALL AREAS DISTURBED BY CONSTRUCTION TO CONDITIONS EQUAL OR BETTER TO THOSE FOUND PRIOR TO CONSTRUCTION.
- THE CONTRACTOR SHALL DETERMINE THE SCOPE, TYPE, SIZE, QUANTITY, METHOD OF INSTALLATION, OPERATION, AND REMOVAL OF THE DEWATERING SYSTEM NECESSARY TO KEEP THE EXCAVATION SITE DEWATERED TO STABILIZE THE SOILS FOR CONSTRUCTION. THE DEWATERING SYSTEM MUST BE LOCATED WITHIN THE CONSTRUCTION EASEMENT.
- THE CONTRACTOR SHALL DISCHARGE WATER FROM THE DEWATERING SYSTEM IN ACCORDANCE WITH THE REQUIREMENTS OF STATE AND LOCAL REGULATIONS AND THE REQUIREMENTS OF THESE PLANS AND SPECIFICATIONS. AT NO TIME SHALL SILT LADEN WATER BE DISCHARGED OFF SITE. SEE EXISTING SITE AND TESC PLAN FOR ADDITIONAL STORMWATER NOTES.
- THE CONTRACTOR SHALL CLEANUP ALL AREAS AFFECTED BY THEIR ACTIVITIES TO THE SATISFACTION OF THE CITY REPRESENTATIVE BY THE END OF EACH WORKING DAY OR MORE FREQUENTLY IF REQUIRED BY THE CITY REPRESENTATIVE. THIS INCLUDES REMOVAL OF ALL DUST, MUD, ROCKS, ASPHALT DEBRIS, AND REFUSE FROM STREETS, SIDEWALKS, DRIVEWAYS, AND ANY OTHER AREAS AFFECTED BY THE CONSTRUCTION ACTIVITIES. FAILURE TO CLEANUP TO THE SATISFACTION OF THE OWNER'S REPRESENTATIVE WILL NECESSITATE A SHUTDOWN OF THE PROJECT UNTIL CLEANUP IS PROPERLY PERFORMED. DAILY CLEANUP IS AN INTEGRAL PART OF EROSION AND POLLUTION CONTROL.
- THE EXISTING LIFT STATION SHALL NOT BE PERMANENTLY TAKEN OUT OF SERVICE, UNTIL THE LIFT STATION CONSTRUCTED UNDER THIS CONTRACT HAS BEEN INSTALLED, TESTED, AND APPROVED IN WRITING BY THE OWNER. A TEMPORARY PUMPING SYSTEM CAN BE INSTALLED DURING CONSTRUCTION TO ALLOW FOR CONSTRUCTION OF THE PROPOSED LIFT STATION TO BE COMPLETED. THE CONTRACTOR SHALL PROVIDE A PLAN TO THE OWNER FOR APPROVAL THAT DETAILS THE PROPOSED METHOD OF KEEPING THE LIFT STATION OPERATIONAL DURING THE CONSTRUCTION WORK. INSTALLATION OF THE TEMPORARY PUMPING SYSTEM SHALL NOT BEGIN UNTIL WRITTEN APPROVAL HAS BEEN OBTAINED FROM THE OWNER. A HIGH LEVEL ALARM FLOAT SHALL BE CONNECTED TO THE EXISTING TELEMETRY SYSTEM FOR PROVIDING NOTIFICATION TO THE OWNER IF THE TEMPORARY SYSTEM HAS FAILED. THE CONTRACTOR MUST RESPOND TO ANY TEMPORARY SYSTEM FAILURE.
- CONTRACTOR SHALL BE RESPONSIBLE FOR ALL SAFETY PRECAUTIONS AND THE METHODS, TECHNIQUES, SEQUENCES AND PROCEDURES REQUIRED TO PERFORM THE WORK.

## SEWER FORCE MAIN CONSTRUCTION NOTES


- GRAVITY MAIN TRENCH, FORCE MAIN TRENCH, AND ALL EXCAVATED AREAS SHALL BE BACKFILLED AND COMPACTED IN ACCORDANCE WITH THESE CONTRACT DOCUMENTS AND WITH SECTIONS 7-9.3(10) AND 7-9.3(11) OF THE STANDARD SPECIFICATIONS. COMPACTION TESTING SHALL BE REQUIRED DURING BACKFILLING OPERATIONS ON ALL PIPE, ALL OPEN CUTS AND/OR CROSSINGS WITHIN PAVED OR TRAVELED AREAS AND AT THE DISCRETION OF THE OWNER. IF TRENCH BACKFILL DOES NOT MEET COMPACTION REQUIREMENTS, CONTRACTOR SHALL EXCAVATE, RE-COMPACT AND RETEST MATERIAL AT CONTRACTOR'S EXPENSE.
- ENGINEER-APPROVED THRUST RESTRAINTS ARE REQUIRED FOR ALL UNRESTRAINED FITTINGS. THRUST BLOCKING IS THE PREFERRED METHOD UNLESS OTHERWISE SHOWN ON THE PLANS. THE CONTRACTOR SHALL PROVIDE ALL NECESSARY PIPE JOINT RESTRAINT SO THAT THE PIPE DOES NOT SEPARATE DUE TO THERMAL EXPANSION, UNRESOLVED THRUST FORCES, OR DESTABILIZATION OF STEEP SLOPES.
- AT POINTS WHERE EXISTING THRUST BLOCKING EXISTS, MINIMUM CLEARANCE OF UNDISTURBED SOIL BETWEEN THE CONCRETE BLOCKING AND PROPOSED BURIED UTILITIES OR STRUCTURES SHALL BE 5 FEET.
- THE CONTRACTOR SHALL PERFORM PRESSURE TESTING IN ACCORDANCE WITH THE SPECIFICATIONS TO 100 PSI FOR THE FORCE MAIN PIPING, UNLESS OTHERWISE APPROVED. THE ENGINEER AND OWNER HAVE DISCRETION TO MODIFY THE TESTING REQUIREMENTS AS DEEMED APPROPRIATE.

## TESC GENERAL NOTES

- REFER TO GENERAL PLAN NOTES FOR ADDITIONAL REQUIREMENTS.
- APPROVAL OF THIS EROSION/SEDIMENTATION CONTROL (ESC) PLAN DOES NOT CONSTITUTE AN APPROVAL OF PERMANENT ROAD OR DRAINAGE DESIGN (E.G. SIZE AND LOCATION OF ROADS, PIPES, RESTRICTORS, CHANNELS, RETENTION FACILITIES, UTILITIES, ETC.).
- THE IMPLEMENTATION OF THESE ESC PLANS AND THE CONSTRUCTION, MAINTENANCE, REPLACEMENT, AND UPGRADING OF THESE ESC FACILITIES IS THE RESPONSIBILITY OF THE APPLICANT/CONTRACTOR UNTIL ALL CONSTRUCTION IS APPROVED, AND THE POTENTIAL FOR ON-SITE EROSION HAS PASSED.
- THE BOUNDARIES OF THE CLEARING LIMITS INDICATED BY THE TEMPORARY CONSTRUCTION EASEMENTS AND THE CITY PROPERTY LINES SHOWN ON THIS PLAN (INCLUDING INDIVIDUAL TREES TO BE SAVED) SHALL BE CLEARLY FLAGGED IN THE FIELD PRIOR TO CONSTRUCTION. DURING THE CONSTRUCTION PERIOD, NO DISTURBANCE BEYOND THE FLAGGED CLEARING LIMITS SHALL BE PERMITTED. THE FLAGGING SHALL BE MAINTAINED BY THE APPLICANT/CONTRACTOR FOR THE DURATION OF CONSTRUCTION.
- THE ESC FACILITIES SHOWN ON THIS PLAN MUST BE CONSTRUCTED AS OUTLINED ON THE TYPICAL CONSTRUCTION SEQUENCE AND IN SUCH A MANNER AS TO INSURE THAT SEDIMENT LADEN WATER DOES NOT ENTER THE DRAINAGE SYSTEM OR VIOLATE APPLICABLE WATER STANDARDS.
- THE ESC FACILITIES SHOWN ON THIS PLAN ARE THE MINIMUM REQUIREMENTS FOR ANTICIPATED SITE CONDITIONS. DURING THE CONSTRUCTION PERIOD, THESE ESC FACILITIES SHALL BE UPGRADED (E.G. ADDITIONAL SUMPS, RELOCATION OF DITCHES AND SILT FENCES, ETC.) AS NEEDED FOR UNEXPECTED STORM EVENTS.
- CONSTRUCTION ACCESS TO THE SITE SHALL BE ONLY AS SHOWN ON THE APPROVED PLANS. ALL VEHICLES LEAVING THE SITE, ONTO PUBLIC RIGHTS OF WAY, SHALL BE CLEANED TO PREVENT "TRACKING" OF MUD, DIRT OR OTHER DEBRIS.
- THE CONTRACTOR SHALL CLEAN ACCESS STREETS AND RIGHT-OF-WAY USING ONLY VACUUM SWEEPERS AT LEAST DAILY OR MORE FREQUENTLY AS MAY BE NECESSARY AND SO DIRECTED BY THE CITY.
- CLEAN OR REMOVE AND REPLACE INLET PROTECTION DEVICES WHEN SEDIMENT HAS FILLED ONE-THIRD OF THE AVAILABLE STORAGE. ALL CATCH BASINS AND CONVEYANCE LINES SHALL BE CLEANED PRIOR TO PAVING. THE CLEANING OPERATION SHALL NOT FLUSH SEDIMENT LADEN WATER INTO THE DOWNSTREAM SYSTEM.
- STOCKPILES ARE TO BE LOCATED IN SAFE AREAS AND ADEQUATELY PROTECTED BY TEMPORARY SECURED PLASTIC COVER, SEEDING OR MULCHING. HYDROSEEDING IS PREFERRED.
- WHERE STRAW MULCH FOR TEMPORARY EROSION CONTROL IS REQUIRED, IT SHALL BE APPLIED AT A MINIMUM THICKNESS OF TWO INCHES.
- ANY AREA STRIPPED OF VEGETATION, INCLUDING ROADWAY EMBANKMENTS, WHERE NO FURTHER WORK IS ANTICIPATED FOR A PERIOD OF 2 DAYS DURING THE WET SEASON OR 7 DAYS DURING THE DRY, SHALL BE IMMEDIATELY STABILIZED WITH THE APPROVED ESC METHODS (E.G. SEEDING, MULCHING, NETTING, EROSION BLANKETS, ETC.).
- VEGETATION SHALL BE ESTABLISHED ON AREAS DISTURBED OR ON AREAS OF CONSTRUCTION AS NECESSARY TO MINIMIZE EROSION. AREAS TO BE ROUGH GRADED WITH FINISHED GRADING TO FOLLOW NEAR PROJECT COMPLETION ARE TO BE SEEDED WITH ANNUAL, PERENNIAL OR HYBRID RYE GRASS. THIS ALSO INCLUDES PERIMETER DIKES AND THE SEDIMENT BASIN EMBANKMENT. HYDROSEEDING IS PREFERRED.
- IMMEDIATELY FOLLOWING FINISH GRADING, PERMANENT VEGETATION WILL BE APPLIED AS APPROVED PER THE APPROVED PLANS, CURRENT WSDOT STANDARDS AND SPECIFICATIONS AND THE CITY OF LYNNWOOD REQUIREMENTS.


## PIPE LENGTH MEASUREMENTS

PIPE LENGTHS CALLED OUT ON PLANS ARE MEASURED AS FOLLOWS:



FITTINGS ARE ASSUMED TO BE STANDARD LENGTH 125#, 250# FLANGED OR COMPACT CLASS 350 MECHANICAL JOINTS. CONTRACTOR RESPONSIBLE FOR VERIFYING LENGTHS. IT IS THE CONTRACTOR'S RESPONSIBILITY TO TAKE INTO ACCOUNT ANY VARIATIONS IN FITTING DIMENSIONS.

## NORTHING AND EASTING POINTS




## EXISTING UTILITIES

- ALL EXISTING UTILITIES INDICATED ON THE PLANS HAVE BEEN PLOTTED FROM THE BEST INFORMATION AVAILABLE TO THE ENGINEER AND SHOULD THEREFORE BE CONSIDERED APPROXIMATE ONLY AND NOT NECESSARILY COMPLETE. THE SOURCE OF INFORMATION GENERALLY CONSISTS OF CONSTRUCTION RECORDS, UTILITY LOCATES, AND OTHER DATA OBTAINED VERBALLY FROM OFFICIALS ASSOCIATED WITH THE PARTICULAR UTILITY. OWNER AND ENGINEER DO NOT GUARANTEE AND DO NOT ASSUME ANY RESPONSIBILITY FOR THE ACCURACY OF THIS INFORMATION. IT IS UNDERSTOOD THAT OTHER ABOVE GROUND AND UNDERGROUND FACILITIES NOT SHOWN ON THE PLANS MAY BE ENCOUNTERED DURING THE COURSE OF THE WORK. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO INDEPENDENTLY VERIFY THE ACCURACY OF ALL UTILITY LOCATIONS SHOWN TO AVOID DAMAGE AND/OR DISTURBANCE TO SUCH UTILITIES, AND TO FURTHER DISCOVER AND AVOID ANY OTHER UTILITIES NOT SHOWN HEREON WHICH MAY BE AFFECTED BY THE IMPLEMENTATION OF THIS PLAN. CONTRACTOR SHALL PRESERVE, PROTECT AND SUPPORT ALL EXISTING UTILITIES ENCOUNTERED DURING CONSTRUCTION.
- OVERHEAD UTILITIES: NOT ALL OVERHEAD UTILITIES MAY BE SHOWN ON THE PLANS. IT IS THE CONTRACTOR'S RESPONSIBILITY TO VISIT THE SITE TO INDEPENDENTLY VERIFY ALL OVERHEAD UTILITIES. THE CONTRACTOR SHALL ACCOUNT FOR ACCOMMODATING ALL OVERHEAD UTILITIES IN HIS BID AND NO ADDITIONAL COMPENSATION WILL BE PROVIDED FOR FACILITATING OVERHEAD UTILITIES.
- POWER AND WATER: WHERE THESE UTILITIES CROSS THE PROPOSED SEWER MAIN, THE DEPTH OF EACH IS SHOWN ON THE PROFILES AND IS BASED ON TYPICAL LAYING DEPTHS FOR EACH OF THESE UTILITIES. ACTUAL DEPTHS ARE UNKNOWN AND MAY VARY SIGNIFICANTLY. CONTRACTOR SHALL NOTIFY THE OWNER IMMEDIATELY IF UTILITY CROSSING DEPTH CONFLICTS ARISE.
- PROVIDE STYROFOAM CUSHION BETWEEN PIPING AT PIPE CROSSINGS WHERE PIPES CROSS WITH FEWER THAN 12 INCHES OF VERTICAL SEPARATION. A SAND CUSHION MAY BE USED IN AREAS WHERE ADEQUATE COMPACTION CAN BE ACHIEVED AND AS APPROVED BY THE OWNER.

## SECTION AND DETAIL REFERENCES

THE FOLLOWING CONVENTIONS HAVE BEEN USED WITHIN THESE DRAWINGS TO REFER THE READER BETWEEN THE SECTION/DETAIL AND THE PLAN FROM WHICH IT IS REFERENCED.

### REFERENCE BUBBLES




WHERE: ID = SECTION/DETAIL REFERENCE NUMBER  
## = DRAWING NUMBER ON WHICH DETAIL ORIGINATED OR RESIDES.

### SECTION/DETAIL REFERENCE NUMBER CONVENTIONS:

SECTIONS OR ELEVATIONS SHOULD HAVE A LETTER REFERENCE NUMBER (A THROUGH ZZ).

DETAILS SHOULD HAVE AN ALPHANUMERIC REFERENCE NUMBER (A-Z OR 1-1799).  
DISCIPLINE SPECIFIC STANDARD DETAILS FOLLOW THE DIVISION NUMBER.

EXAMPLES: 2XX = SITE WORK OR CIVIL STANDARD DETAILS      5XX = STRUCTURAL CONNECTION STANDARD DETAILS  
3XX = CONCRETE STANDARD DETAILS      6XX = MECHANICAL STANDARD DETAILS  
4XX = MASONRY STANDARD DETAILS      7XX = ELECTRICAL STANDARD DETAILS



SIGNED: 03/27/19



SIGNED: 03/27/19

CITY OF LYNNWOOD  
LIFT STATION 8  
IMPROVEMENTS  
GENERAL NOTES AND INFO I



ENGINEER	OMP	REVIEWED	RJF	OMP	RJF	REVIEW
117-288						
JOB NO.:	117-288					
CLIENT:	LYNN					
FILENAME:	LSRD-GEN01.DWG					
DATE:	Mar 26, 2019					
DATE:	Mar 26, 2019					
ISSUED FOR BIDDING						
03/27/19						
NO.						
DATE						
DESCRIPTION						
BY						

CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE


SCALE: SHOWN	
0'	1'
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"	
DWG NO.:	SHEET NO.:
G01	01
	48








**CALL 48 HOURS BEFORE YOU DIG**  
**1-800-424-5555 (811)**  
 UNDERGROUND SERVICE



**EXISTING STORM AND SEWER PLAN VIEW I**  
 1" = 20'



**EXISTING STORM AND SEWER PLAN VIEW II**  
 1" = 20'

**GENERAL NOTES**

- 1) CONTRACTOR MAY PLUG STORMWATER SYSTEM AND USE THE EXISTING STORMWATER DETENTION POND TO TEMPORARILY STORE RUNOFF TRIBUTARY TO THE STORM SYSTEM PROPOSED TO BE REPLACED DURING THIS PROJECT. CONTRACTOR WILL BE RESPONSIBLE FOR REGULARLY PUMPING FROM THE POND TO BYPASS THE SYSTEM UNTIL THE SYSTEM IS INSTALLED AND OPERATIONAL. THE BYPASS CAN BE ROUTED TO THE EXISTING SYSTEM BUT SHALL NOT EXCEED THE MAXIMUM POND DISCHARGE. THE PEAK FLOW INTO THE DETENTION POND FROM A 100-YEAR, 24-HOUR STORM EVENT IS 25.3 CUBIC FEET PER SECOND.
- 2) CONTRACTOR TO SUBMIT BYPASS PUMPING PLAN TO CITY PRIOR TO CONSTRUCTION OF PROPOSED STORM AND SEWER.
- 3) FOR WORK NORTH OF STA 2+50 CONTRACTOR ACCESS TO MALL PROPERTY SHALL BE LIMITED THROUGH LS8 SITE, STORM AND SEWER EASEMENT AND POND PROPERTY. CONTRACTOR SHALL NOT ACCESS THROUGH MALL. ALL WORK NORTH OF STA 2+50 SHALL BE COMPLETED WITHIN THE PERMANENT EASEMENT EXTENTS SHOWN. CONTRACTOR SHALL MAKE ANY/ALL AGREEMENTS TO USE THE AREA OUTSIDE OF THE PERMANENT EASEMENT AT CONTRACTOR'S DISCRETION.




**DEMOLITION NOTES**

- 1 SAWCUT AND REMOVE EXISTING ASPHALT TO SUBGRADE.
  - 2 REMOVE EXISTING CONCRETE TO SUBGRADE AND TO NEAREST JOINT.
  - 3 REMOVE GRAVEL TO NATIVE SOIL OR AS NECESSARY TO CONSTRUCT PROPOSED IMPROVEMENTS.
  - 4 REMOVE AND PROPERLY DISPOSE OF TREE AND ROOT BALL. REMOVE ROOTS AND OTHER ORGANICS AS NECESSARY TO CONSTRUCT PROPOSED IMPROVEMENTS.
  - 5 REMOVE AND PROPERLY DISPOSE OF EXISTING VEGETATION.
  - 6 CLEAR AND GRUB ALL INVASIVE WEEDS AND PLANTS ALONG FENCE LINE AND POND SLOPE.
  - 7 REMOVE AND REPLACE EXISTING CHAINLINK FENCE AND GATE.
  - 8 REMOVE EXISTING GRAVITY SEWER MAIN AS NECESSARY TO CONSTRUCT PROPOSED IMPROVEMENTS.
  - 9 REMOVE EXISTING GRAVITY STORM MAIN AS NECESSARY TO CONSTRUCT PROPOSED IMPROVEMENTS.
  - 10 REMOVE EXISTING MANHOLE OR CATCHBASIN.
  - 11 EXISTING WATER MAIN ASSUMED TO BE ABANDONED. VERIFY LOCATION AND NOTIFY CITY OF ANY CONFLICTS WITH THE PROPOSED IMPROVEMENTS PRIOR TO REMOVAL. CUT AND PLUG WITH GROUT AS NEEDED.
  - 12 ABANDON EXISTING MANHOLES PER STANDARD SPECIFICATION SECTION 7-05.3(2)
  - 13 ABANDON EXISTING SEWER GRAVITY MAIN PER DETAIL ON DWG NO. C13.
  - 14 ABANDON EXISTING STORM MAIN. FILL EXISTING PIPE TO BE ABANDONED WITH GROUT PER THE SPECIAL PROVISIONS.
  - 15 REMOVE AND PROVIDE NEW MONUMENT PER DETAIL ON C12. MONUMENT SHALL BE INSTALLED BY PLS LICENSED IN WASHINGTON
  - 16 EXISTING STORM MAIN IS ASSUMED TO BE ABANDONED. NOTIFY CITY IF STORM PIPE IS IN CONFLICT WITH PROPOSED IMPROVEMENTS.
  - 17 REPLACE PAINT MARKINGS MATCHING EXISTING.
  - 18 DO NOT DISTURB EXISTING HYDRANT.
  - 19 DO NOT DISTURB EXISTING LIGHT.
  - 20 DO NOT DISTURB EXISTING MANHOLE.
  - 21 PROVIDE INLET PROTECTION PER WSDOT STANDARD PLAN I-40.20-00.
  - 22 PROVIDE SILT FENCE PER WSDOT STANDARD PLAN I-30.15-02.
- \*ALL MATERIALS SHALL BE PROPERLY DISPOSED OF AT A CONTRACTOR-PROVIDED DISPOSAL SITE PER WSDOT SPECIFICATION SECTION 2-03.3(7)C

**TRAFFIC CONTROL NOTES**

WORK PERFORMED FROM STATION 0+00 TO 3+00 SHALL BE NIGHT WORK LIMITED TO THE HOURS OF 8 PM TO 5 AM. AT THE END OF WORKING HOURS THE TRENCH SHALL BE PATCHED WITH COLD MIX ASPHALT OR COVERED WITH STEEL PLATES AND VEHICULAR ACCESS RETURNED TO THE MALL. EITHER WALL ROAD OR 188TH ST SW SHALL ALLOW EAST/WEST TRAFFIC MOVEMENTS AND EMERGENCY ACCESS AT ALL TIMES. DURING CONSTRUCTION ONE OF THE ROUTES SHALL REMAIN OPEN AT ALL TIMES FOR EMERGENCY ACCESS. LOCAL POLICE AND FIRE DEPARTMENTS SHALL BE NOTIFIED AT LEAST 48-HOURS IN ADVANCE OF ANY CONSTRUCTION ACTIVITIES.

**VICINITY MAP**



CITY OF LYNNWOOD  
 LIFT STATION 8  
 IMPROVEMENTS  
 LYNNWOOD WASHINGTON  
**STORM & SEWER EXISTING SITE AND DEMOLITION PLAN I**


ENGINEER	OMP	REVISIONS	ISSUED FOR BIDDING	DATE	DESCRIPTION	NO.	DATE	BY	REVIEW
03/27/19	032719	ISSUED FOR BIDDING							

SCALE: SHOWN  
 DRAWING IS FULL SCALE WHEN BAR MEASURES 2"  
 DWG NO.: C01 03 48




**CALL 48 HOURS BEFORE YOU DIG**  
**1-800-424-5555 (811)**  
 UNDERGROUND SERVICE

**TPN 00372600100305**



ALL WORK SHALL BE CONTAINED WITHIN 100' TEMPORARY CONSTRUCTION EASEMENT



**EXISTING STORM AND SEWER PLAN VIEW III**

1" = 20'

**GENERAL NOTES**




- CONTRACTOR MAY PLUG STORMWATER SYSTEM AND USE THE EXISTING STORMWATER DETENTION POND TO TEMPORARILY STORE RUNOFF TRIBUTARY TO THE STORM SYSTEM PROPOSED TO BE REPLACED DURING THIS PROJECT. CONTRACTOR WILL BE RESPONSIBLE FOR REGULARLY PUMPING FROM THE POND TO BYPASS THE SYSTEM UNTIL THE SYSTEM IS INSTALLED AND OPERATIONAL. THE BYPASS CAN BE ROUTED TO THE EXISTING SYSTEM BUT SHALL NOT EXCEED THE MAXIMUM POND DISCHARGE. THE PEAK FLOW INTO THE DETENTION POND FROM A 100-YEAR, 24-HOUR STORM EVENT IS 25.3 CUBIC FEET PER SECOND.
- CONTRACTOR TO SUBMIT BYPASS PUMPING PLAN TO CITY PRIOR TO CONSTRUCTION OF PROPOSED STORM AND SEWER.
- FOR WORK NORTH OF STA 2+50 CONTRACTOR ACCESS TO MALL PROPERTY SHALL BE LIMITED THROUGH LS8 SITE, STORM AND SEWER EASEMENT AND POND PROPERTY. CONTRACTOR SHALL NOT ACCESS THROUGH MALL. ALL WORK NORTH OF STA 2+50 SHALL BE COMPLETED WITHIN THE PERMANENT EASEMENT EXTENTS SHOWN. CONTRACTOR SHALL MAKE ANY/ALL AGREEMENTS TO USE THE AREA OUTSIDE OF THE PERMANENT EASEMENT AT CONTRACTOR'S DISCRETION.

CONTRACTOR SHALL CLOSE ALDERWOOD MALL BLVD AND PROVIDE DETOUR TO CONSTRUCT PROPOSED STORM SYSTEM PER DETOUR AND TRAFFIC CONTROL NOTES ON DWG NOS. TC01 AND TC02.

**DEMOLITION NOTES**

- SAWCUT AND REMOVE EXISTING ASPHALT TO SUBGRADE.
  - REMOVE EXISTING CONCRETE TO SUBGRADE AND TO NEAREST JOINT.
  - REMOVE GRAVEL TO NATIVE SOIL OR AS NECESSARY TO CONSTRUCT PROPOSED IMPROVEMENTS.
  - REMOVE AND PROPERLY DISPOSE OF TREE AND ROOT BALL. REMOVE ROOTS AND OTHER ORGANICS AS NECESSARY TO CONSTRUCT PROPOSED IMPROVEMENTS.
  - REMOVE AND PROPERLY DISPOSE OF EXISTING VEGETATION.
  - CLEAR AND GRUB ALL INVASIVE WEEDS AND PLANTS ALONG FENCE LINE AND POND SLOPE.
  - REMOVE AND REPLACE EXISTING CHAINLINK FENCE AND GATE.
  - REMOVE EXISTING GRAVITY SEWER MAIN AS NECESSARY TO CONSTRUCT PROPOSED IMPROVEMENTS.
  - REMOVE EXISTING GRAVITY STORM MAIN AS NECESSARY TO CONSTRUCT PROPOSED IMPROVEMENTS.
  - REMOVE EXISTING MANHOLE OR CATCHBASIN.
  - EXISTING WATER MAIN ASSUMED TO BE ABANDONED. VERIFY LOCATION AND NOTIFY CITY OF ANY CONFLICTS WITH THE PROPOSED IMPROVEMENTS PRIOR TO REMOVAL. CUT AND PLUG WITH GROUT AS NEEDED.
  - ABANDON EXISTING MANHOLES PER STANDARD SPECIFICATION SECTION 7-05.3(2)
  - ABANDON EXISTING SEWER GRAVITY MAIN PER DETAIL ON DWG NO. C13.
  - ABANDON EXISTING STORM MAIN. FILL EXISTING PIPE TO BE ABANDONED WITH GROUT PER THE SPECIAL PROVISIONS.
  - REMOVE AND PROVIDE NEW MONUMENT PER DETAIL ON C12. MONUMENT SHALL BE INSTALLED BY PLS LICENSED IN WASHINGTON
  - EXISTING STORM MAIN IS ASSUMED TO BE ABANDONED. NOTIFY CITY IF STORM PIPE IS IN CONFLICT WITH PROPOSED IMPROVEMENTS.
  - REPLACE PAINT MARKINGS MATCHING EXISTING.
  - DO NOT DISTURB EXISTING HYDRANT.
  - DO NOT DISTURB EXISTING LIGHT.
  - DO NOT DISTURB EXISTING MANHOLE.
  - PROVIDE INLET PROTECTION PER WSDOT STANDARD PLAN I-40.20-00.
  - PROVIDE SILT FENCE PER WSDOT STANDARD PLAN I-30.15-02.
- \*ALL MATERIALS SHALL BE PROPERLY DISPOSED OF AT A CONTRACTOR-PROVIDED DISPOSAL SITE PER WSDOT SPECIFICATION SECTION 2-03.3(7)C

**VICINITY MAP**




**CITY OF LYNNWOOD**  
**LIFT STATION 8 IMPROVEMENTS**  
**STORM & SEWER EXISTING SITE AND DEMOLITION PLAN II**



ENGINEER	OMP	REVIEWED	DATE	DESCRIPTION
REVISIONS	ISSUED FOR BIDDING			
03/27/19				





**EXISTING SITE PLAN**  
1" = 10'

**DEMOLITION NOTES**


- 1 SAWCUT EXISTING ASPHALT.
  - 2 REMOVE EXISTING ASPHALT TO SUBGRADE.
  - 3 REMOVE EXISTING CONCRETE TO SUBGRADE AND TO NEAREST JOINT.
  - 4 REMOVE GRAVEL TO NATIVE SOIL OR AS NECESSARY TO MEET ELEVATIONS ON DWG NO. C10.
  - 5 REMOVE AND PROPERLY DISPOSE OF TREE AND ROOT BALL. REMOVE ROOTS AND OTHER ORGANICS AS NECESSARY TO CONSTRUCT PROPOSED IMPROVEMENTS.
  - 6 REMOVE AND PROPERLY DISPOSE OF EXISTING RETAINING WALL.
  - 7 REMOVE AND PROPERLY DISPOSE OF EXISTING CHAIN LINK FENCE.
  - 8 EXISTING YARD HYDRANT AND APPURTENANCES TO BE REMOVED. REMOVE METER AND SERVICE LINE TO WATER MAIN AND ABANDON EXISTING CORP STOP.
  - 9 REMOVE AND PROPERLY DISPOSE OF EXISTING GRAVITY SEWER MAIN. MAIN SHALL BE LEFT IN SERVICE UNTIL NEW GRAVITY SEWER INSTALLATION.
  - 10 EXISTING LIFT STATION TO BE DECOMMISSIONED.
  - 11 REFER TO DWG NO. C04 FOR ADDITIONAL DETAILS ON LIFT STATION DEMOLITION AND ABANDONMENT. ANY FITTINGS REMOVED SHALL BE PROPERLY DISPOSED OF.
  - 12 REMOVE AND PROPERLY DISPOSE OF EXISTING POSTS.
  - 13 REMOVE AND PROPERLY DISPOSE OF EXISTING BOLLARDS.
  - 14 REMOVE EXISTING ROOF, CONCRETE PAD AND ELECTRICAL EQUIPMENT. RETURN ELECTRICAL AND ELECTRONIC EQUIPMENT TO CITY.
  - 15 REMOVE AND PROPERLY DISPOSE OF EXISTING STAIRCASE.
  - 16 DO NOT DISTURB EXISTING POWER.
  - 17 DO NOT DISTURB EXISTING LIGHT. CONDUITS FOR LIGHT WERE NOT FOUND. FIELD LOCATE ON LS8 SITE PRIOR TO EXCAVATION. CONTRACTOR TO NOTIFY CITY OF ANY CONFLICTS ONCE LOCATED.
  - 18 DO NOT DISTURB EXISTING SIDEWALK.
  - 19 DO NOT DISTURB EXISTING FENCE.
  - 20 PROVIDE INLET PROTECTION PER WSDOT STANDARD PLAN 1-40-20-00
  - 21 CONSTRUCTION STAGING AREA.
- \*ALL MATERIALS SHALL BE PROPERLY DISPOSED OF AT A CONTRACTOR-PROVIDED DISPOSAL SITE PER WSDOT SPECIFICATION SECTION 2-03.3(7)C

**NOTES**

- REFER TO DWG NO. C04 FOR CAMERA SHOT LOCATIONS.
- CONTRACTOR IS RESPONSIBLE FOR BUOYANCY CONTROL DURING LIFT STATION ABANDONMENT AND DEMOLITION.
- PROVIDE TRAFFIC CONTROL AS NECESSARY FOR DEMOLITION AND CONSTRUCTION OF THE PROPOSED DRIVEWAY ENTRANCE. TRAFFIC CONTROL SHALL BE LIMITED TO A SINGLE LANE CLOSURE. LANE CLOSURE SHALL BE PER CITY OF LYNNWOOD STANDARD DETAIL STD7-4 ON DWG NO. TC02.
- THE EXISTING LIFT STATION SHALL BE ACCESSIBLE BY CITY CREWS AND A CITY VACTOR TRUCK AT ALL TIMES FOR THE DURATION OF CONSTRUCTION.

**KEY NOTES**


- A APPROX. 40 LF OF EXISTING ROCK RETAINING WALL TO BE REMOVED.
  - B APPROX. 3,090 SF OF EXISTING GRAVEL TO BE REMOVED.
  - C APPROX. 75 SF OF EXISTING ASPHALT TO BE REMOVED.
  - D APPROX. 224 LF OF EXISTING FENCING TO BE REMOVED.
- \*NOTE: QUANTITIES DO NOT INCLUDE REMOVAL FOR STORM AND SEWER REPLACEMENT.



REVISIONS	ISSUED FOR BIDDING	DATE	DESCRIPTION	BY	REVIEW
1	03/27/19		ISSUED FOR BIDDING		

**CALL 48 HOURS BEFORE YOU DIG**  
1-800-424-5555 (811)  
UNDERGROUND SERVICE





**EXISTING LIFT STATION DEMOLITION PLAN**  
NOT TO SCALE

- EXISTING PUMP STATION REMOVAL AND ABANDONMENT NOTES:**
1. NOT ALL EQUIPMENT, PIPING, AND OTHER APPURTENANCES ARE SHOWN IN THIS VIEW.
  2. REMOVE ALL PUMPS, PIPES, FITTINGS, ELECTRICAL AND TELEMETRY EQUIPMENT, LADDERS, FANS AND ALL OTHER APPURTENANCES FROM INSIDE THE PUMP STATION. THE EXISTING PUMP STATION RISER ACCESS SHALL BE REMOVED AND THE PUMP STATION COMPLETELY FILLED WITH SAND SLURRY OR CDF.
  3. DELIVER REMOVED PUMPS, MOTORS, AND GATE VALVES TO CITY SHOPS. OTHER ITEMS SHALL BE PROPERLY DISPOSED.
  4. ALL MATERIALS SHALL BE PROPERLY DISPOSED OF AT A CONTRACTOR-PROVIDED DISPOSAL SITE PER WSDOT SPECIFICATION SECTION 2-03.3(7)C

EXISTING GRAVITY INFLUENT PIPE TO BE REMOVED TO THE LIMITS SHOWN ON DWG NO. C03

DO NOT DISTURB EXISTING GRAVITY INFLUENT PIPE

DO NOT DISTURB EXISTING CONCRETE SLAB

EXISTING MANHOLE TO BE MODIFIED PER DETAILS ON DWG NOS. M02 AND M03. ANY EXISTING PENETRATIONS UNUSED FOR THE PROPOSED STATION SHALL BE GROUTED.

EXISTING GRAVITY MAIN WAS ABANDONED PER SKILLINGS CONNOLLY RECORD DRAWINGS. REMOVE AS NECESSARY TO CONSTRUCT PROPOSED IMPROVEMENTS.

EXISTING ELECTRICAL SHELTER AND COMPONENTS TO BE REMOVED

EXISTING PIPE TO BE REMOVED

EXISTING ELECTRICAL CONDUITS TO BE ABANDONED IN PLACE

EXISTING BEND TO BE REMOVED

EXISTING PIPE TO BE REMOVED

OUTLINE OF EXISTING PUMP STATION TO BE ABANDONED

EXISTING PUMPS TO BE REMOVED AND RETURNED TO CITY SHOPS

EXISTING APPURTENANCES TO BE REMOVED AND RETURNED TO CITY SHOPS



**EXISTING SITE PHOTO**

EXISTING FENCE TO BE REMOVED

EXISTING GATE TO BE REMOVED

EXISTING STAIR CASE TO BE REMOVED

EXISTING SHELTER TO BE REMOVED


EXISTING BOLLARDS TO BE REMOVED

EXISTING BYPASS PORT TO BE PROTECTED IN PLACE

EXISTING YARD HYDRANT TO BE REMOVED. COORDINATE WITH CITY REPRESENTATIVE FOR WATER SHUT OFF



**EXISTING SITE PHOTO**



**EXISTING LIFT STATION OBLIQUE**  
NOT TO SCALE

EXISTING DRY WELL TOP AND RISER TO BE REMOVED. REMOVE RISER DOWN 8- FEET BELOW THE EXISTING RIM ELEVATION

EXISTING BYPASS PORT TO BE PROTECTED IN PLACE. CONTRACTOR MAY UTILIZE PORT FOR BYPASS PUMPING EFFORTS AFTER OBTAINING APPROVAL FROM THE CITY.

EXISTING WET WELL TO BE MODIFIED

EXISTING PIPE TO BE REMOVED

EXISTING FORCEMAIN TO BE PROTECTED IN PLACE

EXISTING GATE VALVE AND TEE TO BE PROTECTED IN PLACE

PRIOR TO USING THE BYPASS PORT FOR BYPASS PUMPING INSTALL BLIND FLANGES AND THRUST BLOCKING PER DWG NO. M02

EXISTING FITTING TO BE REMOVED

EXISTING PIPE TO BE REMOVED

EXISTING PUMP STATION TO BE ABANDONED

PROPOSED PIPE PENETRATIONS. SEE DWG NOS. M02 AND M04 FOR DETAILS

EXISTING CHAMFER IN WET WELL TO BE REMOVED (NOT SHOWN)



**EXISTING SITE PHOTO**




**EXISTING SITE PHOTO**

**CALL 48 HOURS BEFORE YOU DIG**  
1-800-424-5555 (811)  
UNDERGROUND SERVICE


ENGINEER	OMP	REVIEWED	RJF	OMP	RJF	REVIEW
DATE: Mar 26, 2019	DATE: Mar 26, 2019	DATE: Mar 26, 2019	DATE: Mar 26, 2019	DATE: Mar 26, 2019	DATE: Mar 26, 2019	DATE: Mar 26, 2019
FILENAME: LSR-D-0101.DWG	ISSUED FOR BIDDING					
DESCRIPTION						





**EXISTING STORM AND SEWER PLAN VIEW I**

1" = 20'




**SEWER CENTERLINE PROFILE I**

H: 1" = 20', V: 1" = 5'

**GENERAL NOTES**

- EXISTING UTILITIES HAVE NOT BEEN POTHOLED TO IDENTIFY LOCATION, MATERIAL, SIZE OR GEOMETRY.
- PIPE SLOPES ARE REFERENCING ACTUAL LAYING SLOPE OF PIPE BETWEEN EDGE OF STRUCTURES. PIPE LENGTHS ARE REFERENCED TO CENTER OF STRUCTURES PER PAYMENT LENGTH.
- TRENCH SECTION AND PAVEMENT RESTORATION FOR STORM AND SEWER SHALL BE PER LYNNWOOD STANDARD PLANS ON DWG NO. C11 AND C12.
- STORM PIPE MATERIAL SHALL BE PER SPECIFICATIONS SECTION 7-04.
- SEWER CONNECTIONS TO THE PROPOSED MANHOLES SHALL BE PER DETAIL ON DWG NO. C13.
- IF THE CONTRACTOR CHOOSES TO USE HDPE PIPE FOR SEWER, PIPE BLOCKING SHALL BE ADDED TO EACH MANHOLE STRUCTURES FOR EACH PIPE PENETRATION, SEE DETAILS ON DWG NO. S01.
- REFER TO SPECIAL PROVISIONS 7-08.3(1)D REGARDING POTHOLING AT UTILITY CROSSINGS A SUFFICIENT DISTANCE AHEAD OF PIPE-LAYING.

**VICINITY MAP**



SCALE: SHOWN  
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"  
DWG NO.: C05 SHEET NO.: 07

CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE



**RH2 ENGINEERING**  
40 YEARS SINCE 1978  
BOTHELL, WA  
22722 29th Drive SE, Suite 210  
www.rh2.com 1.800.720.8052

**RICHARD BALDWIN**  
32878  
REGISTERED PROFESSIONAL ENGINEER  
SIGNED: 03/27/19

**BOWEN BALDWIN**  
38889  
REGISTERED PROFESSIONAL ENGINEER  
SIGNED: 03/27/19


CITY OF LYNNWOOD  
LIFT STATION 8 IMPROVEMENTS  
STORM & SEWER PLAN AND PROFILE I




ENGINEER	OMP	REVISIONS	ISSUED FOR BIDDING	DATE	NO.	DESCRIPTION	BY	REVIEW
03/27/19	03/27/19	1						

JOB NO.: 117-288  
CLIENT: LYNN  
FILENAME: LSR-D-UTLIP.DWG  
DATE: Mar 26, 2019  
PLOT DATE: Mar 27, 2019







**EXISTING STORM AND SEWER PLAN VIEW II**  
1" = 20'



**SEWER CENTERLINE PROFILE II**  
H: 1" = 20', V: 1" = 5'



**CALL 48 HOURS BEFORE YOU DIG**  
1-800-424-5555 (811)  
UNDERGROUND SERVICE




**CITY OF LYNNWOOD**  
**LIFT STATION 8 IMPROVEMENTS**  
**STORM & SEWER PLAN AND PROFILE II**

**GENERAL NOTES**

- EXISTING UTILITIES HAVE NOT BEEN POTHOLED TO IDENTIFY LOCATION, MATERIAL, SIZE OR GEOMETRY.
- PIPE SLOPES ARE REFERENCING ACTUAL LAYING SLOPE OF PIPE BETWEEN EDGE OF STRUCTURES. PIPE LENGTHS ARE REFERENCED TO CENTER OF STRUCTURES PER PAYMENT LENGTH.
- TRENCH SECTION AND PAVEMENT RESTORATION FOR STORM AND SEWER SHALL BE PER LYNNWOOD STANDARD PLANS ON DWG NO. C11 AND C12.
- STORM PIPE MATERIAL SHALL BE PER SPECIFICATIONS SECTION 7-04.
- SEWER CONNECTIONS TO THE PROPOSED MANHOLES SHALL BE PER DETAIL ON DWG NO. C13.
- IF THE CONTRACTOR CHOOSES TO USE HDPE PIPE FOR SEWER, PIPE BLOCKING SHALL BE ADDED TO EACH MANHOLE STRUCTURES FOR EACH PIPE PENETRATION, SEE DETAILS ON DWG NO. S01.
- REFER TO SPECIAL PROVISIONS 7-08.3(1)D REGARDING POTHOLING AT UTILITY CROSSINGS A SUFFICIENT DISTANCE AHEAD OF PIPE-LAYING.


**VICINITY MAP**



ENGINEER	OMP	REVISIONS	ISSUED FOR BIDDING	DATE	NO.	DESCRIPTION
OMP	OMP	OMP	OMP	03/27/19	1	ISSUED FOR BIDDING


SCALE: SHOWN  
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"  
DWG NO.: C06 SHEET NO.: 08 OF 48






**EXISTING STORM AND SEWER PLAN VIEW III**

1" = 20'



**SEWER CENTERLINE PROFILE III**

H: 1" = 20', V: 1" = 5'




**STORM CENTERLINE PROFILE**

H: 1" = 20', V: 1" = 5'

**GENERAL NOTES**

- EXISTING UTILITIES HAVE NOT BEEN POTHOLED TO IDENTIFY LOCATION, MATERIAL, SIZE OR GEOMETRY.
- PIPE SLOPES ARE REFERENCING ACTUAL LAYING SLOPE OF PIPE BETWEEN EDGE OF STRUCTURES. PIPE LENGTHS ARE REFERENCED TO CENTER OF STRUCTURES PER PAYMENT LENGTH.
- TRENCH SECTION AND PAVEMENT RESTORATION FOR STORM AND SEWER SHALL BE PER LYNNWOOD STANDARD PLANS ON DWG NO. C11 AND C12.
- STORM PIPE MATERIAL SHALL BE PER SPECIFICATIONS SECTION 7-04.
- SEWER CONNECTIONS TO THE PROPOSED MANHOLES SHALL BE PER DETAIL ON DWG NO. C13.
- IF THE CONTRACTOR CHOOSES TO USE HDPE PIPE FOR SEWER, PIPE BLOCKING SHALL BE ADDED TO EACH MANHOLE STRUCTURES FOR EACH PIPE PENETRATION, SEE DETAILS ON DWG NO. S01
- REFER TO SPECIAL PROVISIONS 7-08.3(1)D REGARDING POTHOLING AT UTILITY CROSSINGS A SUFFICIENT DISTANCE AHEAD OF PIPE-LAYING.

**VICINITY MAP**



**RH2 ENGINEERING**  
40 YEARS SINCE 1978  
BOTHELL, WA  
22722 29th Drive SE, Suite 210  
www.rh2.com 1.800.720.8052

**Richard Ballard**  
REGISTERED PROFESSIONAL ENGINEER  
SIGNED: 03/27/19

**Bowin Hall**  
REGISTERED PROFESSIONAL ENGINEER  
SIGNED: 03/27/19

CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE

CITY OF LYNNWOOD  
LIFT STATION 8 IMPROVEMENTS  
STORM & SEWER PLAN AND PROFILE III

ENGINEER	OMP	REVIEWED	ISSUED FOR BIDDING	DATE	DESCRIPTION	BY	REVIEW
LYNN	117-088	LSR-D-UTLIP.DWG	03/27/19				



SCALE: SHOWN

DRAWING IS FULL SCALE WHEN BAR MEASURES 2"

DWG NO.: C07 SHEET NO.: 09 OF 48















CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE



CITY OF LYNNWOOD  
LYNNWOOD WASHINGTON  
LIFT STATION 8 IMPROVEMENTS

STORM & SEWER SECTIONS




SECTION VIEWS  
H: 1" = 10', V: 1" = 10'

ENGINEER: OMP	DATE: Mar 26, 2019	CLIENT: LYNN	JOB NO.: 117288	REVISIONS	NO.	DATE	DESCRIPTION	BY	REVIEW
REVIEWED: RJF	FILE NAME: LSRD-LUTLP.DWG	ISSUED FOR BIDDING	03/27/19	1					
				SCALE: SHOWN					
				DRAWING IS FULL SCALE WHEN BAR MEASURES 2"					
DWG NO.: C08				SHEET NO.: 10					



POINT TABLE			
POINT NO.	NORTHING	EASTING	DESCRIPTION
1	304145.31	1286451.90	GATE POST
2	304168.04	1286477.40	MAN GATE POST
3	304165.96	1286478.99	FENCE CORNER
4	304138.80	1286443.35	FENCE CORNER
5	304177.34	1286414.03	FENCE CORNER
6	304204.48	1286449.63	FENCE CORNER
7	304108.64	1286466.29	FENCE CORNER
8	304157.71	1286472.31	SITE LIGHT
9	304125.69	1286488.25	BOLLARD
10	304118.72	1286479.08	BOLLARD
11	304129.41	1286496.45	BOLLARD
12	304126.12	1286498.96	BOLLARD
13	304145.95	1286438.63	WET WELL VENT
14	304146.75	1286438.03	WET WELL VENT
15	304145.52	1286449.23	HOSE BIB



SIGNED: 03/27/19



SIGNED: 03/27/19

CITY OF LYNNWOOD  
LIFT STATION 8  
IMPROVEMENTS  
**PROPOSED SITE PLAN**



ENGINEER	DATE	REVISIONS	ISSUED FOR BIDDING	DATE	DESCRIPTION	BY	REVIEW
ENGINEER: KRP	DATE: Mar 27, 2019	REVISIONS: REF	ISSUED FOR BIDDING	03/27/19			
JOB NO.: 117-288	CLIENT: LYNN	FILENAME: LSR-D-DWG02.DWG					
DWG NO.: C09	SHEET NO.: 11						

TYPE 8 JUNCTION BOX TO BE INSTALLED BY OTHERS  
FORCE MAIN (GRAY) HAS BEEN CONSTRUCTED BY OTHERS AND STUBBED INTO THE SITE. CONTRACTOR MUST VERIFY LOCATION PRIOR TO MAKING FINAL CONNECTION

BOLLARD, TYP. OF 2. PROVIDE MIN. 2' CLEARANCE TO EXISTING BYPASS PUMPING PORT. FIELD LOCATE WITH CITY REPRESENTATIVE

PROVIDE (4) HYDRAULIC BOLLARDS AT 46" O.C. BOLLARD TO BE AMERISTAR TITAN ANTI-RAM HYDRAULIC BOLLARDS OR APPROVED EQUAL. INSTALL PER MANUFACTURER'S REQUIREMENTS


BOLLARD FOOTING, APPROX. DIMENSIONS 6'-0"W x 16'-2"L x 6'-6"D. ADJUST DIMENSIONS PER MANUFACTURER'S REQUIREMENTS.

PROVIDE NEW SERVICE LINE, METER AND SETTER PER CITY STANDARD DRAWING 5-2 ON DWG NO. C12. SIZE TO MATCH EXISTING.

PROVIDE APPROX. 58 LF OF COPPER TYPE K LINE FOR WATER SERVICE. FIELD LOCATE RPBA AND FROST PROOF YARD HYDRANT WITH CITY REPRESENTATIVE. PROVIDE FITTINGS AS NECESSARY FOR A COMPLETE WORKING SYSTEM

APPROX. LOCATION OF BOLLARD HYDRAULIC POWER UNIT. FIELD LOCATE WITH CITY REPRESENTATIVE

BOLLARD, TYP. OF 6. PROVIDE MIN. 1' CLEARANCE TO EXISTING BYPASS PUMPING PORT AND HPU. FIELD LOCATE WITH CITY REPRESENTATIVE



**PROPOSED SITE PLAN**  
1" = 5'

**CALL 48 HOURS BEFORE YOU DIG**  
1-800-424-5555 (811)  
UNDERGROUND SERVICE

PROPOSED EMERGENCY GENERATOR, REFER TO DWG NO. E08

400 E08 BOLLARD, TYP. OF 7.

PROPOSED CHECK VALVE VAULT TYP. OF 2

APPROX. 124 LF OF 8-FOOT TALL AMERISTAR MONTAGE II CLASSIC 4 RAIL FENCE, TYP. ON NORTHWEST, NORTHEAST AND SOUTHEAST OF PUMP STATION

PROPOSED ELECTRICAL SHELTER (ROOF OUTLINE), REFER TO DETAILS ON DWG NO. S05

PROVIDE APPROX. 86 LF OF 10-FOOT TALL CHAIN LINK FENCE WITH PRIVACY SLATS ALONG SOUTHWEST PROPERTY LINE

YARD HYDRANT


PROPOSED ELECTRICAL JUNCTION BOX  
PROPOSED WETWELL TYP. OF 2

PROPOSED GRAVITY PIPE PER DWG NO. M02, TYP.

PROVIDE RPBA PER CITY STANDARD DRAWING 5-12B ON DWG NO. C12. FIELD LOCATE WITH CITY REPRESENTATIVE. CONTRACTOR SHALL PROVIDE ADDITIONAL FREEZE PROOFING AT THE CITY'S DISCRETION


EXISTING MANHOLE TO BE MODIFIED PER DWG NO. M02





SITE POINTS				
POINT NO.	NORTHING	EASTING	ELEVATION	DESCRIPTION
16	304198.05	1286445.39	385.65	EG PAD CORNER
17	304189.42	1286451.95	385.65	EG PAD CORNER
18	304182.89	1286459.22	385.50	VALVE VAULT CORNER
19	304177.05	1286463.66	385.50	VALVE VAULT CORNER
20	304166.26	1286449.46	385.50	VALVE VAULT CORNER
21	304172.10	1286445.02	385.50	VALVE VAULT CORNER
22	304166.98	1286465.46	385.50	WETWELL CENTER
23	304156.18	1286451.26	385.50	WETWELL CENTER
24	304159.09	1286481.51	385.39	METER MANHOLE CENTER
25	304134.26	1286496.39	384.44	POLYPIG VAULT CORNER
26	304136.48	1286499.31	384.44	POLYPIG VAULT CORNER
27	304181.57	1286422.06	385.65	ELECTRICAL SHELTER CORNER
28	304176.76	1286415.73	385.65	ELECTRICAL SHELTER CORNER
29	304145.10	1286449.15	385.65	JUNCTION BOX PAD CORNER
30	304146.96	1286447.74	385.65	JUNCTION BOX PAD CORNER
31	304115.39	1286474.70	384.02	PAVING LIMITS
32	304081.66	1286467.61	MATCH EXISTING	PAVING LIMITS
33	304119.86	1286517.74	MATCH EXISTING	PAVING LIMITS
34	304119.45	1286496.75	383.69	PAVING LIMITS
35	304120.85	1286495.68	383.66	PAVING LIMITS
36	304141.87	1286498.52	384.84	PAVING LIMITS
37	304154.00	1286514.43	384.96	PAVING LIMITS
38	304166.72	1286504.73	385.00	PAVING LIMITS
39	304154.60	1286488.83	385.40	PAVING LIMITS
40	304166.53	1286479.74		CENTER POINT
41	304125.51	1286504.71		CENTER POINT
42	304129.96	1286507.48		CENTER POINT
43	304103.20	1286458.74		CENTER POINT

**PROPOSED SITE PLAN**  
1" = 5'





PROVIDE 20' DRIVEWAY ENTRANCE PER CITY STANDARD DRAWING STD3-121

PROVIDE CURB RAMP PER CITY STANDARD DRAWING STD3-121, TYP. EA SIDE OF DRIVEWAY. REFER TO DETAIL FOR GRADING


ADJUST GAS VALVE TO FINISHED GRADE

**CALL 48 HOURS BEFORE YOU DIG**  
1-800-424-5555 (811)  
UNDERGROUND SERVICE




ENGINEER OMP	DATE: Mar 26, 2019	CLIENT: LYNN	JOB NO.: 117-288
REVIEWED: RJF	DATE: Mar 26, 2019	FILENAME: LSR-D-DWG03.DWG	
<b>REVISIONS</b>			
NO.	DATE	DESCRIPTION	BY
1	03/27/19	ISSUED FOR BIDDING	RJF
SCALE: SHOWN			
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"			
DWG NO.:	C10	SHEET NO.:	12
			48







	SILT FENCE		DRAWING NUMBER	STD2-5
			SCALE	NONE
			REVISION DATE	11/05
			DEPARTMENT	PW




	5' - 7' COMMERCIAL AT-GRADE DRIVEWAY		DRAWING NUMBER	STD3-12A
			SCALE	NONE
			REVISION DATE	04/17
			DEPARTMENT	PW




	TYPICAL TRENCH SECTION IN RIGHT-OF-WAY		DRAWING NUMBER	STD6-12
			SCALE	NONE
			REVISION DATE	04/14
			DEPARTMENT	PW



	BEDDING FOR PIPE IN TRENCHES		DRAWING NUMBER	STD6-13
			SCALE	NONE
			REVISION DATE	03/14
			DEPARTMENT	PW



	SEWER MANHOLE COVER		DRAWING NUMBER	STD6-7
			SCALE	NONE
			REVISION DATE	06/14
			DEPARTMENT	PW



	TYPICAL TRENCH COMPACTION		DRAWING NUMBER	STD6-17
			SCALE	NONE
			REVISION DATE	01/14
			DEPARTMENT	PW



	TYPE D CURB RAMP		DRAWING NUMBER	STD3-15A
			SCALE	NONE
			REVISION DATE	03/14
			DEPARTMENT	PW

40 YEARS SINCE 1978

BOTHELL, WA 98043
   
 22722 29th Drive SE, Suite 210
   
 www.rh2.com 1.800.720.8052

RICHARD J. BALLARD
   
 32878
   
 REGISTERED PROFESSIONAL ENGINEER
   
 SIGNED: 03/27/19

RYAN J. PETERS
   
 49451
   
 REGISTERED PROFESSIONAL ENGINEER
   
 SIGNED: 03/27/19

CITY OF LYNNWOOD
   
 LIFT STATION 8 IMPROVEMENTS

**TESC AND CIVIL DETAILS**


ENGINEER	OMP	DATE	Mar 26, 2019	CLIENT	LYNN	DWG NO.	117-088
REVIEWER	RJF	DATE	Mar 27, 2019	FILENAME	LSR-D-DET.DWG		
<b>REVISIONS</b>							
ISSUED FOR BIDDING	OMP	RJF		BY		DATE	

SCALE: SHOWN

DRAWING IS FULL SCALE WHEN BAR MEASURES 2"

DWG NO.: C11
   
 SHEET NO.: 13
   
 48






- NOTES**
- ALL TRENCHES IN ROADWAY AREAS SHALL BE BACKFILLED AND PATCHED WITH TEMPORARY ASPHALT AT THE END OF EACH WORK DAY, UNLESS PERMISSION IS GRANTED TO DO OTHERWISE BY THE CITY.
  - ALL TEMPORARY PATCHES ON TRENCHES SHALL BE PERMANENTLY PATCHED AS SOON AS POSSIBLE UPON COMPLETION OF WORK WITHIN THE ROADWAY AREA.
  - REPLACE AND RESTORE ALL SURFACE IMPROVEMENTS (I.E. TRAFFIC BUTTONS, CURBING, STRIPING) AS DIRECTED BY THE CITY.
  - IF THERE ARE MORE THAN 3 PARALLEL OR PERPENDICULAR PATCHES PROPOSED WITHIN 100 LINEAL FEET OF ROADWAY, THE DEVELOPER SHALL BE RESPONSIBLE TO GRIND AND OVERLAY THE ENTIRE AREA TO PUBLIC WORKS STANDARDS.
  - SEE COL STD 3-18C FOR PAVEMENT PATCHING REQUIREMENTS ON ARTERIALS AND OVERLAYS LESS THAN 5 YEARS OLD OR COL STD 3-18B FOR ALTERNATE PATCH DETAIL TO STD 3-18C.

**LYNNWOOD WASHINGTON** PUBLIC WORKS

PAVEMENT PATCHING DETAILS

DRAWING NUMBER	STD3-18A
SCALE	NONE
REVISION DATE	12/16
DEPARTMENT	PW




- NOTE:**
- COMPRESSION FITTING (OR APPROVED EQUAL). USE STAINLESS STIFFENER WITH POLYPIPE. BAND CLAMPS AND BARBED FITTINGS NOT ALLOWED.
  - CORPORATION STOPS: DIRECT TAP WITH DUCTILE IRON. DIRECT TAP AWWA CC TAPER THREAD INLET X MALE IRON PIPE THREAD OUTLET #FB400-3 3/4\"/>

**LYNNWOOD WASHINGTON** PUBLIC WORKS

3/4\"/>

DRAWING NUMBER	STD5-1
SCALE	NONE
REVISION DATE	03/17
DEPARTMENT	PW




- NOTE:**
- ROMAC AND MUELLER DOUBLE STRAP SERVICE SADDLES WITH C.C. THREAD OR I.P. THREAD TO BE USED ON ALL MAINS.
  - CORPORATION STOPS: 1 1/2\"/>


**LYNNWOOD WASHINGTON** PUBLIC WORKS

1 1/2\"/>

DRAWING NUMBER	STD5-2
SCALE	NONE
REVISION DATE	05/06
DEPARTMENT	PW



**1\"/>**




- NOTES**
- FOR A 4FT X 4FT PATCH MINIMUM, USE TENSAR GLASGRID 8501 AT BASE OF WEARING COURSE. PLACE TACK COAT UNDERNEATH GLASGRID. FOLLOW MANUFACTURE RECOMMENDATIONS.
  - ALL TRENCHES IN ROADWAY AREAS SHALL BE BACKFILLED AND PATCHED WITH TEMPORARY ASPHALT AT THE END OF EACH WORK DAY, UNLESS PERMISSION IS GRANTED TO DO OTHERWISE BY THE CITY.
  - ALL TEMPORARY PATCHES ON TRENCHES SHALL BE PERMANENTLY PATCHED AS SOON AS POSSIBLE UPON COMPLETION OF WORK WITHIN THE ROADWAY AREA.
  - REPLACE AND RESTORE ALL SURFACE IMPROVEMENTS (I.E. TRAFFIC BUTTONS, CURBING, STRIPING) AS DIRECTED BY THE CITY.
  - IF THERE ARE MORE THAN 3 PARALLEL OR PERPENDICULAR PATCHES PROPOSED WITHIN 100 LINEAL FEET OF ROADWAY, THE DEVELOPER SHALL BE RESPONSIBLE TO GRIND AND OVERLAY THE ENTIRE AREA TO PUBLIC WORKS STANDARDS.

**LYNNWOOD WASHINGTON** PUBLIC WORKS

PAVEMENT PATCHING ALTERNATIVE DETAILS

DRAWING NUMBER	STD3-18B
SCALE	NONE
REVISION DATE	07/14
DEPARTMENT	PW




FITTING D	90°	45°	22 1/2°	11 1/4°
6"	4 SQ FT	6 SQ FT	3 SQ FT	2 SQ FT
8"	7 SQ FT	10 SQ FT	6 SQ FT	3 SQ FT
10"	10 SQ FT	15 SQ FT	9 SQ FT	5 SQ FT
12"	14 SQ FT	22 SQ FT	12 SQ FT	6 SQ FT
16"	25 SQ FT	38 SQ FT	21 SQ FT	11 SQ FT
18"	32 SQ FT	32 SQ FT	27 SQ FT	14 SQ FT

- NOTES:**
- BEARING AREA TABLE BASED ON 250 PSI PRESSURE AND 2000 PSF SOIL BEARING. IF PRESSURE IS GREATER OR SOIL BEARING IS LESS, THE THRUST BLOCK SIZE SHALL BE INCREASED.
  - THIS TABLE REPRESENTS THE 'MINIMUM' CONSTRUCTION STANDARDS. THE DEVELOPER'S ENGINEER SHALL BE RESPONSIBLE FOR DETERMINING THE APPROPRIATE SIZE OF ALL THRUST BLOCKS BASED ON EXISTING AND LOCAL CONDITIONS.
  - ALL BLOCKS ON TEES MUST BE SEPARATED FOR DIRECTION OF THRUST. SHEET PLASTIC OVER NUTS AND BOLTS PRIOR TO CONCRETE POUR.
  - ALL FITTING TO HAVE THRUST BLOCKING AND ALL THRUST BLOCKS TO BE FORMED AND ARE TO BE POURED IN PLACE.
  - BLOCKS TO BE FORMED AS REQUIRED BY LYNNWOOD INSPECTOR.

**LYNNWOOD WASHINGTON** PUBLIC WORKS

HORIZONTAL THRUST BLOCKS

DRAWING NUMBER	STD5-5
SCALE	NONE
REVISION DATE	11/01
DEPARTMENT	PW




- NOTES:**
- Cross connection control assembly shall be located immediately downstream of water meter box prior to any branch connections, with no more than 1'-2" between boxes. Alternate location allowed with approval from Public Works.
  - Back flow assemblies must be selected from Washington State Department of Health list of Backflow assemblies approved for installation in Washington State.
  - After installation of the backflow assembly, the developer or installer will call the Lynnwood Public Works Department for an inspection.
  - Following an Inspection Approval by the Public Works Department, the backflow assembly must be scheduled for an initial test by a Washington State Certified Backflow Assembly Tester. Meter must be installed prior to testing.
  - RPBA must be purchased and installed as a unit. No modifications to any part of the assembly are allowed.
  - Freeze protection is the responsibility of the owner and shall not interfere with operation or testing of the assembly.
  - Pipe from meter to RPBA shall be copper or brass.
  - Unions must be installed vertically or horizontally. Dielectric unions must be used to separate dissimilar materials.
  - The installer/developer must provide test cock protection with plugs, caps or covers.
  - Minimum 12" gap from bottom of relief port to top of daylight drain.
  - Backflow assembly to be installed within 2' of water meter unless approved by the City.

**LYNNWOOD WASHINGTON** PUBLIC WORKS

2\"/>

DRAWING NUMBER	STD 5-12B
SCALE	NONE
REVISION DATE	04/14
DEPARTMENT	PW




- NOTES:**
- THE OFF-STREET MONUMENT SHALL BE THE SAME EXCEPT USING A NO. 8 REBAR AND WITHOUT A CASE AND COVER. THE OFF-STREET MONUMENT SHALL BE 3" ABOVE GRADE.
  - MONUMENT CASE AND COVER SHALL BE CAST IRON.
  - BRASS DISC SHALL BEAR LAND SURVEYOR'S REGISTRATION NUMBER.


**LYNNWOOD WASHINGTON** PUBLIC WORKS

SURVEY MONUMENT

DRAWING NUMBER	STD3-17
SCALE	NONE
REVISION DATE	11/01
DEPARTMENT	PW



SIGNED: 03/27/19




SIGNED: 03/27/19



ENGINEER	OMP	REVIEWED	RJF	DATE	03/27/19	DESCRIPTION	ISSUED FOR BIDDING						
DATE	Mar 26, 2019	CLIENT	LYNN	JOB NO.	117-288	FILENAME	LSR-D-D-DET.DWG						
REVISIONS	<table border="1"> <tr> <th>NO.</th> <th>DATE</th> <th>DESCRIPTION</th> </tr> <tr> <td>1</td> <td></td> <td></td> </tr> </table>							NO.	DATE	DESCRIPTION	1		
NO.	DATE	DESCRIPTION											
1													






**FORCEMAIN**

**GRAVITY MAIN**



**SEWER ABANDONMENT**  
NOT TO SCALE

100  
C09




**SECURITY MAN GATE DETAIL**  
NOT TO SCALE

103  
C09




**CURB RAMP DETAILS**  
NOT TO SCALE

106  
C09





**SEWER MANHOLE CONNECTION DETAIL**  
NOT TO SCALE

101  
---




**SECURITY FENCE DETAIL**  
NOT TO SCALE

104  
C09




**GANTRY V-TRACK DETAIL**  
NOT TO SCALE

107  
C09



**HOT MIX ASPHALT PAVEMENT SECTION**  
NOT TO SCALE

102  
C09



**CHAIN LINK FENCE DETAIL**  
NOT TO SCALE

105  
C09

**RH2 ENGINEERING**  
40 YEARS SINCE 1978

BOTHELL, WA 98041  
227723 29th Drive SE, Suite 210  
www.rh2.com 1.800.720.8052

32878

REGISTERED PROFESSIONAL ENGINEER

SIGNED: 03/27/19

32878

REGISTERED PROFESSIONAL ENGINEER

SIGNED: 03/27/19

CITY OF LYNNWOOD  
LIFT STATION 8 IMPROVEMENTS

LYNNWOOD WASHINGTON

**CIVIL DETAILS II**


REVISIONS	DATE	DESCRIPTION	BY	REVIEW
ISSUED FOR BIDDING	03/27/19			

SCALE: SHOWN

DRAWING IS FULL SCALE WHEN BAR MEASURES 2"

DWG NO. C13 SHEET NO. 15





**PLAN VIEW**  
APPROX. SCALE: 1" = 250'

**ADVANCED WARNING SIGN SPACING**

ROAD TYPE	SPEED	DISTANCES BETWEEN ADVANCED WARNING SIGNS*			
		A**	B**	C**	D**
RURAL ROADS	55 45	500 FT. ±	500 FT. ±	500 FT. ±	500 FT. ±
RURAL ROADS AND URBAN ARTERIALS	40 35	350 FT. ±	350 FT. ±	350 FT. ±	N/A
RURAL ROADS, URBAN STREETS, RESIDENTIAL BUSINESS DISTRICTS	30 25	200 FT. ***	200 FT. ***	200 FT. ***	N/A
URBAN STREETS	25 OR LESS	100 FT. ***	100 FT. ***	100 FT. ***	N/A

\*ALL SPACING MAY BE ADJUSTED TO ACCOMMODATE INTERCHANGE RAMPS, AT-GRADE INTERSECTIONS, AND DRIVEWAYS.  
 \*\*THIS REFERS TO THE DISTANCE BETWEEN ADVANCE WARNING SIGNS. SEE FIGURE 1 PER WAC 296-155-305. TYPICAL LANE CLOSURE ON TWO-LANE ROAD. THIS SITUATION IS TYPICAL FOR ROADWAYS WITH SPEED LIMITS LESS THAN 45 MPH.  
 \*\*\*THIS SPACING MAY BE REDUCED IN URBAN AREAS TO FIT ROADWAY CONDITIONS.  
 EXEMPTION: IN A MOBILE FLAGGING OPERATION, AS DEFINED BY THE MUTCD WHEN THE FLAGGER IS MOVING WITH THE OPERATION, THE "FLAGGER AHEAD (SYMBOL OR TEXT)" SIGN MUST BE:  
 • WITHIN 1,500 FEET OF THE FLAGGER; AND  
 • THE FLAGGER STATION MUST BE SEEN FROM THE SIGN.

**CALL 48 HOURS BEFORE YOU DIG**  
1-800-424-5555 (811)  
UNDERGROUND SERVICE

**SIGN LEGEND**

- 1\* 1L 1R • WSDOT TYPE 3 BARRICADE PER WSDOT STANDARD PLAN K-80.20-00 WITH DETOUR SIGN (M4-10 L OR R) AND ROAD CLOSED SIGN (R11-4) ATTACHED  
• 1\* INDICATES THAT SIGN M4-10 IS NOT REQUIRED ON THE INDICATED BARRICADE
- 2 • WSDOT TYPE 3 BARRICADE PER WSDOT STANDARD PLAN K-80.20-00 WITH ROAD CLOSED SIGN (R11-2) ATTACHED
- 3 • CUSTOM SIGN MEETING THE REQUIREMENTS SET FORTH IN THE MUTCD AND THE WSDOT SIGN FABRICATION MANUAL
- 4 • W20-3
- 5 • W20-2
- 6L 6R • M4-9
- 7 • MODIFIED M4-9
- 8 • M4-8A
- 9L 9R • R9-11 (L OR R INDICATES ARROW DIRECTION)
- 10 • R9-9


**DETOUR NOTES**

- ALL TRAFFIC CONTROL DEVICES ARE REQUIRED TO MEET THE LATEST EDITION OF THE MUTCD.
- ALL BARRICADES ARE TO HAVE AMBER FLASHING LIGHTS SECURELY ATTACHED TO THE BARRICADE PER WSDOT STANDARD PLAN K80.20-00.
- PROVIDE EMERGENCY VEHICLE ACCESS TO ALL ADJACENT PROPERTIES AND BUILDINGS WITHIN THE SCOPE OF THIS PROJECT. NOTIFY LOCAL POLICE AND FIRE DEPARTMENTS AT LEAST 48 HOURS IN ADVANCE OF ANY ACTIONS BY THE CONTRACTOR WHICH MAY AFFECT THEIR FUNCTIONS. PROVIDE 20-FOOT WIDE ACCESS FOR EMERGENCY VEHICLES THROUGH ALDERWOOD MALL BLVD WHEN WORK IS NOT ACTIVELY BEING PERFORMED, INCLUDING NIGHT ACCESS.
- PROVIDE ACCESS FOR ALL BUSINESSES AND PATRONS REQUIRING ACCESS FROM ALDERWOOD MALL PARKWAY DURING ROAD CLOSURE. NOTIFY BUSINESSES AT LEAST 48 HOURS IN ADVANCE TO ANY TRENCH WORK AFFECTING ACCESS TO THEIR PROPERTY.
- PROVIDE A SAFE AND ACCESSIBLE ROUTE THROUGH THE CONSTRUCTION AREA FOR PEDESTRIANS. PROVIDE SIGNAGE AS NECESSARY PER THE MUTCD. ALL TEMPORARY PEDESTRIAN ROUTES SHALL MEET ALL REQUIREMENTS OF THE ADA STANDARDS. PEDESTRIANS SHALL BE ROUTED ALONG THE INTERURBAN TRAIL.
- SIGN PLACEMENT IS APPROXIMATE. LOCATE SIGNS IN A MANNER TO AVOID CONFLICTS WITH DRIVEWAYS, SIDEWALKS, UTILITIES AND EXISTING SIGNAGE. ENSURE ALL TEMPORARY SIGNAGE IS CLEARLY VISIBLE TO DRIVERS.
- IF WORK IS REQUIRED OUTSIDE THE WORK ZONE CLOSED TO TRAFFIC, THE CONTRACTOR SHALL COORDINATE WITH THE CITY AND SUBMIT TRAFFIC CONTROL PLANS FOR APPROVAL. ANY APPROVED LANE CLOSURES MUST MEET CITY STANDARD DETAILS ON DWG NO. TC02.
- THIS TRAFFIC CONTROL PLAN ASSUMES THAT THE ROAD WILL REMAIN CLOSED FOR THE DURATION SPECIFIED IN THE SPECIAL PROVISIONS. IF LANES ARE OPENED TO TRAFFIC AND THE WORK ZONE INCLUDES OR USES GROOVED PAVEMENT, ABRUPT LANE EDGES, STEEL PLATES, OR GRAVEL OR EARTH SURFACES, THE CONSTRUCTION ZONE MUST BE POSTED WITH SIGNS STATING THE CONDITIONS, AS REQUIRED BY CURRENT LAW, AND IN ADDITION MUST WARN MOTORCYCLISTS OF THE POTENTIAL HAZARD. SIGNS INCLUDED BUT NOT LIMITED TO "MOTORCYCLES USE EXTREME CAUTION" (W21-1701), "CAUTION STEEL PLATE ON ROADWAY" (W21-1801), "FRESH OIL" (W21-2), AND "GROOVED PAVEMENT" (W8-15) MUST BE USED IN ADDITION TO THE TRAFFIC CONTROL SIGNS SHOWN ON THESE PLANS.

ENGINEER	DATE	REVISIONS	ISSUED FOR BIDDING	DATE	DESCRIPTION
OMP	Mar 25, 2019				
REVIEWED	Mar 26, 2019				
DATE					
BY					
REVIEW					

SCALE: SHOWN  
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"  
DWG NO.: TC01 SHEET NO.: 16 OF 48






**LYNNWOOD WASHINGTON** PUBLIC WORKS

TRAFFIC CONTROL PLAN  
2 LANE ROADWAY; ONE LANE CLOSED WITH ALTERNATING ONE-WAY TRAFFIC AND FLAGGERS


DRAWING NUMBER: STD7-1  
SCALE: NONE  
REVISION DATE: 06/10  
DEPARTMENT: PW



**LYNNWOOD WASHINGTON** PUBLIC WORKS

TRAFFIC CONTROL PLAN  
2 LANE ROADWAY; PARTIAL LANE CLOSURE


DRAWING NUMBER: STD7-2  
SCALE: NONE  
REVISION DATE: 06/10  
DEPARTMENT: PW



**LYNNWOOD WASHINGTON** PUBLIC WORKS

TRAFFIC CONTROL PLAN  
2 LANE ROADWAY WITH CENTER TURN LANE WITH LANE CLOSED


DRAWING NUMBER: STD7-4A  
SCALE: NONE  
REVISION DATE: 04/13  
DEPARTMENT: PW



**LYNNWOOD WASHINGTON** PUBLIC WORKS

TRAFFIC CONTROL PLAN  
5 LANE ROADWAY WITH RIGHT LANE CLOSED

DRAWING NUMBER: STD7-4  
SCALE: NONE  
REVISION DATE: 04/13  
DEPARTMENT: PW



**LYNNWOOD WASHINGTON** PUBLIC WORKS

TRAFFIC CONTROL DEVICES

DRAWING NUMBER: STD7-13  
SCALE: NONE  
REVISION DATE: 06/11  
DEPARTMENT: PW

**RH2 ENGINEERING** 40 YEARS SINCE 1978

BOTHELL, WA  
22722 29th Drive SE, Suite 210  
www.rh2.com 1.800.720.8052

**RICHARD HALLARD**  
STATE OF WASHINGTON  
REG. NO. 3287  
REGISTERED PROFESSIONAL ENGINEER

SIGNED: 03/27/19

**RAIN J. PETERS**  
STATE OF WASHINGTON  
REG. NO. 49451  
REGISTERED PROFESSIONAL ENGINEER

SIGNED: 03/27/19

CITY OF LYNNWOOD  
LIFT STATION 8 IMPROVEMENTS

**TRAFFIC CONTROL DETAILS**

**LYNNWOOD WASHINGTON**

ENGINEER	OMP	REVIEWED	DATE	DESCRIPTION	BY	REVIEW
OMP	OMP	RJF				
03/27/19	ISSUED FOR BIDDING					

JOB NO.: 117-088  
CLIENT: LYNN  
FILENAME: LSR-D-DET.DWG

**REVISIONS**

SCALE: SHOWN

DRAWING IS FULL SCALE WHEN BAR MEASURES 2"

DWG NO.: TC02  
SHEET NO.: 17



# GENERAL STRUCTURAL NOTES

200  
TYP.

**GEOTECHNICAL PARAMETERS:**  
 MINIMUM FROST DEPTH 18"  
 MAXIMUM SOIL BEARING CAPACITY: 2,000 PSF  
 SOILS REPORT REFERENCE "ENGINEERING GEOLOGY REPORT" PREPARED BY RH2 ENGINEERING

**OTHER LOADING PARAMETERS:**  
 WIND LOAD 105 MPH, EXPOSURE C  
 SNOW LOAD 25 PSF  
 EARTHQUAKE LOAD LAT 47.825, LONG 122.274, SOIL PROFILE TYPE C

**OTHER DESIGN VALUES USED:**  
 OCCUPANCY CATEGORY III, WASTE WATER FACILITY  
 CONCRETE 4,000 PSI WITH 60,000 PSI REINFORCING  
 CMU 1,500 PSI WITH 60,000 PSI REINFORCING  
 STEEL A36 FOR PLATES, A992 FOR OTHER

**LIVE LOADS:**  
 ROOF 20 PSF

**CRITERIA:**  
 ALL MATERIALS, WORKMANSHIP, DESIGN, AND CONSTRUCTION SHALL CONFORM TO THE DRAWINGS, SPECIFICATIONS, AND THE INTERNATIONAL BUILDING CODE (2012 EDITION)

**SPECIAL INSPECTIONS, TESTS, AND OBSERVATIONS:**  
 SPECIAL INSPECTIONS AND TESTS SHALL INCLUDE THE FOLLOWING. REFER TO IBC SECTION 1704 AND 1705 FOR DETAILS.  
 1. SPECIAL INSPECTIONS BY THE GEOTECHNICAL ENGINEER INCLUDING:  
 1.1. SITE EXCAVATION AND GRADING  
 1.2. PLACEMENT OF STRUCTURAL FILL AND SOIL COMPACTION  
 1.3. VERIFICATION OF SOIL-BEARING CAPACITY  
 2. CONCRETE PLACEMENT AT CONCRETE CONSTRUCTION: CONTINUOUS, SEE ALSO SECTION 1705.3 OF THE INTERNATIONAL BUILDING CODE.  
 3. REINFORCEMENT AT CONCRETE CONSTRUCTION: PERIODIC, SEE ALSO SECTION 1705.3.  
 4. TESTING OF CONCRETE FOR SPECIFIED COMPRESSIVE STRENGTH (FC), AIR CONTENT AND SLUMP. SEE ALSO TABLE 1705.3.  
 5. STRUCTURAL OBSERVATION BY A REGISTERED DESIGN PROFESSIONAL IN ACCORDANCE WITH IBC 1704.5 SHALL BE PROVIDED.  
 6. CONCRETE ANCHOR INSPECTION SHALL BE PER THE SPECIFICATIONS 3.15.19.

**GENERAL:**  
 LINES SHOWN ON DRAWINGS MAY BE ASSOCIATED WITH CAD MODELING AND MAY NOT REPRESENT REQUIRED OR ALLOWED JOINTS. SEE DETAILS FOR CLARIFICATION ON REQUIRED AND ALLOWED JOINTS.

**REINFORCED CONCRETE:**  
 1. REINFORCING STEEL SHALL BE DETAILED (INCLUDING HOOKS AND BENDS) IN ACCORDANCE WITH ACI 315-99 AND 318-11. LAP ALL REINFORCEMENTS IN ACCORDANCE WITH THE "REINFORCING SPLICE AND DEVELOPMENT LENGTH SCHEDULE" - SEE THIS SHEET. LAP ADJACENT MATS OF WELDED WIRE FABRIC A MINIMUM OF 8" AT SIDES AND ENDS.  
 2. NO BARS PARTIALLY EMBEDDED IN HARDENED CONCRETE SHALL BE FIELD BENT UNLESS SPECIFICALLY DETAILED OR APPROVED BY THE STRUCTURAL ENGINEER.  
 3. A 6" WATERSTOP SHALL BE PLACED AT ALL BELOW GRADE CONCRETE SLAB AND WALL CONSTRUCTION JOINTS AND AS SHOWN TO PROVIDE A WATERTIGHT STRUCTURE.  
 4. CONCRETE PROTECTION FOR REINFORCING STEEL SHALL BE AS FOLLOWS, UNLESS OTHERWISE NOTED:  
 4.1. FOOTINGS AND OTHER UNIFORMED SURFACES CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH ..... 3"  
 4.2. FORMED SURFACES EXPOSED TO EARTH (WALLS BELOW GRADE), WATER OR WEATHER (#6 BARS OR LARGER) ..... 2"  
 4.3. COLUMN TIES OR SPIRALS AND BEAM STIRRUPS ..... 2"  
 4.4. SLABS AND INTERIOR FACES ..... 2"

**ABBREVIATIONS:**  
 AL - ALUMINUM  
 CHK - CHECKERED  
 CL - CENTERLINE  
 CLR - CLEAR  
 EA - EACH  
 EF - EACH FACE  
 FB - FLAT BAR  
 GALV - GALVANIZED  
 HORZ - HORIZONTAL  
 LLV - LONG LEG VERT  
 O.C. - ON CENTER  
 PL - PLATE  
 RB - ROUND BAR  
 RST - REINF. STEEL  
 SST - STAINLESS STEEL  
 T&B - TOP & BOTTOM  
 VERT - VERTICAL

REINFORCEMENT SPLICE AND DEVELOPMENT SCHEDULE					
BAR	Ld, MINIMUM STRAIGHT DEVELOPMENT LENGTHS			MINIMUM LAP SPLICE LENGTHS	
	MINIMUM	TOP BARS	OTHERWISE	CLASS A	CLASS B
#3	19"	25"	29"	Ld	1.3xLd
#4	24"	32"	36"	Ld	1.3xLd
#5	29"	38"	43"	Ld	1.3xLd
#6	42"	55"	63"	Ld	1.3xLd

\*"MINIMUM" IF:  
 MIN COVER OF ONE BAR Ø AND MIN SPACING OF TWO BAR DIAMETERS  
 MIN COVER ONE Ø, MIN SPACING OF ONE BAR Ø, AND TIES OR STIRRUPS LESS THAN 12" OF FRESH CONCRETE BELOW HORIZONTAL BARS  
 "TOP BARS" IF:  
 MEETS CRITERIA FOR MIN EXCEPT 12" OR MORE FRESH CONC BELOW  
 "OTHERWISE" IF:  
 DOES NOT MEET REQUIREMENTS FOR MIN DEVELOPMENT LENGTH  
 "CLASS A" IF:  
 ONLY HALF OF BARS LAPPED AT ONE LOCATION AND TWICE THE REINFORCING FOR TENSION IS PROVIDED  
 "CLASS B" IF:  
 LAP SPLICES DO NOT MEET CLASS A REQUIREMENTS

CONCRETE ANCHORS SHALL BE EITHER HILTI HIT-RE 500-V3 INJECTABLE MORTAR, SIMPSON STRONG-TIE SET-XP ANCHORING ADHESIVE, OR POWERS PE1000+ ADHESIVE ANCHORS AS SPECIFIED. WHERE SIZE IS CALLED OUT ON THE DRAWINGS, PROVIDE MINIMUM EMBEDMENT DEPTHS AS SHOWN ON THE FOLLOWING TABLES. PROVIDE MINIMUM EDGE DISTANCES AND SPACING AS SHOWN ON THE FOLLOWING TABLE UNLESS SPECIFICALLY DETAILED OTHERWISE.

INSTALL ANCHORS IN STRICT ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.


NOTIFY OWNER 24 HOURS IN ADVANCE OF INSTALLATION OF ALL ANCHORS.

WHERE SIZE IS NOT CALLED OUT, ANCHOR SHALL BE SELECTED BASED ON DESIGN LOADS. IF THE MINIMUM EDGE DISTANCE AND/OR MINIMUM SPACING CAN NOT BE ACHIEVED, REFER TO PRODUCT INFORMATION FOR REDUCTION IN ALLOWABLE LOADS.

CONCRETE ANCHORS HILTI HIT-RE 500-V3, SIMPSON STRONG-TIE SET-XP & POWERS PE1000+					
DIA. OF ROD (INCHES) OR REBAR SIZE NO.	MIN. EDGE DISTANCE (INCHES)	MIN. EMBEDMENT (INCHES)	MIN. ANCHOR SPACING (INCHES)	ALLOWABLE LOAD BASED ON BOND STRENGTH (POUNDS)	
				TENSION	SHEAR
1/2	2-1/2	2-3/4	2-1/2	1,027	2,210
5/8	3-1/8	3-1/8	3-1/8	1,312	2,827
3/4	3-3/4	3-1/2	3-3/4	1,556	3,351
7/8	4-3/8	3-1/2	4-3/8	1,556	3,351
#4	2-1/2	4-1/2	2-1/2	1,520	3,618
#5	3-1/8	5-5/8	3-1/8	1,775	5,494
#6	3-3/4	6-3/4	3-3/4	2,225	7,570
#7	4-3/8	7-7/8	4-3/8	2,440	9,428
#8	5	9	5	4,520	11,507

## CONCRETE ANCHOR

201  
TYP.



### SIZING TABLE

PIPE DIA.	T (min)	L (min)
24"	12"	60"
30"	12"	66"
36"	12"	72"

NOTE: NOT ALL SIZES SHOWN. PIPE SIZES SHALL BE BASED ON OUTSIDE PIPE DIAMETER.


## PIPE BLOCKING

NOT TO SCALE

205  
TYP.

PIPE BLOCKING NOTES:


- DETAIL SHALL BE USED AT ALL STRUCTURE PENETRATIONS WHERE HDPE PIPE IS USED FOR GRAVITY SEWER AND STORM PIPE AND AS SPECIFIED ON THE PLANS. WHERE ADJACENT STRUCTURE IS A MANHOLE, CONCRETE ANCHORS SHALL BE SIMILAR TO MANHOLE DETAIL ON THIS SHEET.
- CONCRETE BLOCK SHALL BE PER SECTION 7-09.3(21) OF THE WSDOT STANDARD SPECIFICATIONS.
- MAINTAIN 18" MINIMUM COVER OVER THE TOP OF BLOCK.
- BOTTOM OF BLOCK IS TO BE ON UNDISTURBED SOIL.
- TRENCH TO BE BACKFILLED TO THE FULL DEPTH OF THE BLOCK WITH CRUSHED ROCK COMPACTED TO 95% DENSITY ON ALL SIDES OF BLOCK AND TO A MINIMUM DISTANCE OF 4' IN FRONT OF AND BEHIND PROPOSED BLOCK.
- FOR SOIL CONDITIONS NOT SHOWN, BLOCK IS TO BE DESIGNED BY THE ENGINEER.
- IF BLOCK CANNOT BE KEYED INTO UNDISTURBED SOIL TO THE SATISFACTION OF THE ENGINEER:
  - THE BLOCK LENGTH SHALL BE EXTENDED TO PROVIDE AN ADEQUATE KEY OR
  - CDF SHALL BE USED TO FILL BACK TO NATIVE SOIL OR
  - THE TRENCH SHALL BE BACKFILLED AND COMPACTED TO 95% DENSITY A MINIMUM DISTANCE OF 15 FEET IN FRONT OF THE BLOCK TO THE SATISFACTION OF THE ENGINEER.
- HDPE WALL RING MUST BE SIZED TO RESIST PULL-OUT FORCE OF HDPE PIPE DUE TO THERMAL EXPANSION AND PIPELINE CHARGING PER MANUFACTURER'S RECOMMENDATION.



## PENETRATION AND OPENING REINFORCEMENT

NOT TO SCALE


203  
TYP.




## EQUIPMENT PAD

1" = 1'-0"

204  
TYP.



SIGNED: 03/27/19



SIGNED: 03/27/19


CITY OF LYNNWOOD  
 LIFT STATION 8  
 IMPROVEMENTS  
 LYNNWOOD WASHINGTON  
**STRUCTURAL GENERAL NOTES AND DETAILS**

DATE	DESCRIPTION	BY	REVIEW
03/27/19	ISSUED FOR BIDDING	OMP	RUF


**CALL 48 HOURS BEFORE YOU DIG**  
 1-800-424-5555 (811)  
 UNDERGROUND SERVICE



CALL 48 HOURS  
BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE



**LIFT STATION 8 STRUCTURAL PLAN**  
1/4" = 1'-0"



ACCESS HATCH SCHEDULE							
NO.	CLEAR OPENING	NO. OF LEAVES	RATING	MOUNTING*	SAFETY CHAIN**	QUANTITY	GASKET
H201	72" x 108"	2	H-20	BOLTS	YES	2	ODOR TIGHT
H202	60" x 84"	2	H-20	ANCHOR	YES	2	STANDARD
H203	48" x 72"	2	H-20	ANCHOR	YES	1	STANDARD
H204	36" x 36"	2	H-20	ANCHOR	NO	1	STANDARD
H205	48" x 72"	2	H-20	BOLTS	YES	1	ODOR TIGHT

ACCESS HATCH NOTES:  
\* ACCESS HATCHES OVER STRUCTURES EXPOSED TO RAW SEWAGE SHALL BE MOUNTED USING STAINLESS STEEL. OTHER ACCESS HATCH SHALL BE MOUNTED USING THE STANDARD FRAME ANCHORS THAT COME WITH THE HATCH.  
\*\* SAFETY CHAINS SHALL BE PROVIDED ON ACCESS HATCHES AS SHOWN IN DETAIL


CITY OF LYNNWOOD  
LIFT STATION 8  
IMPROVEMENTS  
STRUCTURAL PLAN



REVISIONS			
NO.	DATE	DESCRIPTION	BY
1	03/27/19	ISSUED FOR BIDDING	OMP




CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE




SIGNED: 03/27/19




SIGNED: 03/27/19




**WET WELL PLAN**  
1/2" = 1'-0"



**METER MANHOLE PLAN**  
1/2" = 1'-0"



**WET WELL SECTION**  
1/2" = 1'-0"



**METER MANHOLE SECTION**  
1/2" = 1'-0"

CITY OF LYNNWOOD  
LIFT STATION 8  
IMPROVEMENTS  
STRUCTURAL SECTIONS I



ENGINEER	DATE	REVISIONS	ISSUED FOR BIDDING	DATE	DESCRIPTION	BY	REVIEW
DND	Mar 26, 2019	1	ISSUED FOR BIDDING	03/27/19			
JMC	Mar 26, 2019	2					




CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE



CONCRETE RISER, THICKNESS TO MATCH THE EXISTING WET WELL. VERIFY HEIGHT PRIOR TO ORDERING SO LID MEETS FINISHED GRADE ELEVATIONS ON THIS SHEET


LEVEL BEARING SURFACE OF RISER AND ALLOW TO CURE PRIOR TO PLACING BENTONITE SEAL AND RISER. INSTALL CONTINUOUS SWELLSTOP BETWEEN WET WELL RISER AND EXISTING CONCRETE. GROUT INTERIOR AND EXTERIOR FACE OF JOINT PER SPECIFICATIONS DIVISION 9. CONTRACTOR TO PROVIDE 12" CONCRETE COLLAR IF NECESSARY AS DETERMINED BY THE ENGINEER.



EXISTING WET WELL WALL

EXISTING WET WELL CHAMFER TO BE REMOVED. REFER TO ADDITIONAL INFORMATION ON DWG NO. C04. INSTALL NEW GROUT PER DWG NO. M04

EXISTING WET AND DRY WELL BASE TO BE RETAINED IN PLACE



**EXISTING WET WELL MODIFICATIONS**  
1/2" = 1'-0" (A S02)

SEE DWG NO. S02 FOR ACCESS HATCH SCHEDULE

PRECAST CONCRETE LID. DIAMETER TO MATCH EXISTING WET WELL

ASPHALT PER THE PROPOSED SITE PLAN ON DWG NO. C09


CRUSHED SURFACING PER THE PROPOSED SITE PLAN ON DWG NO. C09

CONTRACTOR-DESIGNED DEEP SHORING SYSTEM. SEE SPECIFICATIONS DIVISION 2.50 FOR ADDITIONAL INFORMATION, TYP.


CONTROLLED DENSITY FILL

BACKFILL MATERIAL AROUND EXISTING WET AND DRY WELLS IS UNKNOWN.

EXISTING DRYWELL TO BE ABANDONED PER NOTES ON DWG NO. C04



**PIG/BYPASS PORT SECTION**  
1/2" = 1'-0" (B S02)



**EXISTING WET WELL PLAN**  
1/2" = 1'-0"



CITY OF LYNNWOOD  
LIFT STATION 8 IMPROVEMENTS  
LYNNWOOD WASHINGTON

**STRUCTURAL SECTIONS II**


NO.	DATE	DESCRIPTION	BY	REVIEW
1	03/27/19	ISSUED FOR BIDDING	OMP	RJF




CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE




**ELECTRICAL SHELTER FRONT ELEVATION**  
3/4" = 1'-0"



**ELECTRICAL SHELTER SIDE ELEVATION**  
3/4" = 1'-0"



**BASE PLATE DETAIL**  
3" = 1'-0"



**ELECTRICAL SHELTER PLAN**  
3/8" = 1'-0"

CITY OF LYNNWOOD  
LIFT STATION 8 IMPROVEMENTS  
ELECTRICAL SHELTER STRUCTURAL DETAILS















































REVISIONS	DATE	DESCRIPTION	BY	REVIEW
03/27/19	ISSUED FOR BIDDING			



## GENERAL MECHANICAL NOTES

1. CONTRACTOR SHALL PROVIDE ALL NECESSARY EQUIPMENT, MATERIALS, LABOR, AND EXPERTISE TO CONSTRUCT MAJOR AND MINOR PIPING SYSTEMS ACCORDING TO APPLICABLE CODES, STANDARDS, AND MANUFACTURER RECOMMENDATIONS.
2. CONTRACTOR SHALL CONFORM TO PIPE ROUTING AND ARRANGEMENT AS CLOSELY AS POSSIBLE. CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFY ALL PIPING DIMENSIONS. CONTRACTOR SHALL PREPARE AND SUBMIT DETAILED DIMENSIONAL DRAWINGS BASED ON APPROVED EQUIPMENT AND PIPING SYSTEMS.
3. NOT ALL PIPING, VALVES, FITTING AND ACCESSORIES ARE SHOWN. PROVIDE ALL PIPE, VALVES, AND ACCESSORIES AS SHOWN ON THE PROCESS AND INSTRUMENTATION (P&ID) DRAWINGS EVEN THOUGH NOT SHOWN ON MECHANICAL DRAWINGS.
4. FITTINGS AND/OR PIPING THAT MAY BE REQUIRED IN ORDER TO OPERATE SOME MINOR MECHANICAL SYSTEMS, INSTRUMENTATION, AND EQUIPMENT MAY NOT BE SHOWN IN THE PLANS. THE CONTRACTOR SHALL PROVIDE FITTINGS AND PIPING AS NECESSARY TO HAVE A COMPLETE AND FUNCTIONAL SYSTEM.
5. CONTRACTOR SHALL CONNECT EQUIPMENT, VALVES, METERS, AND OTHER SIMILAR FITTINGS TO PIPING SYSTEM SUCH THAT IT CAN BE READILY DISASSEMBLED FOR MAINTENANCE OF THE EQUIPMENT. THIS MAY REQUIRE PROVIDING ADDITIONAL FITTINGS OR SUPPORTS NOT SHOWN IN THE PLANS.
6. DISMANTLING JOINTS OR FLANGE COUPLING ADAPTORS WITH SHACKLE RODS MAY BE ADDED WITH ENGINEER APPROVAL TO FACILITATE PIPE ASSEMBLY.
7. CONTRACTOR SHALL PROVIDE VALVED VENTS AT HIGH POINTS AND VALVED DRAINS AT LOW POINTS AND ALL OTHER LOCATIONS AS NECESSARY TO SUCCESSFULLY TEST PIPING SYSTEMS.
8. PIPING, VALVES, SUPPORTS, AND OTHER APPURTENANCE HARDWARE THAT WILL BE SUBMERGED DURING NORMAL OPERATING CONDITIONS SHALL BE STAINLESS STEEL, UNLESS OTHERWISE NOTED.
9. NOT ALL PIPE SUPPORTS ARE SHOWN IN THE PLANS. CONTRACTOR SHALL PROVIDE AND INSTALL PIPE SUPPORTS AS NECESSARY TO PROVIDE A RIGID, SECURE, NON-SAGGING SYSTEM. SEE SPECIFICATIONS FOR ADDITIONAL INFORMATION.
10. FITTING TAPS SHALL BE DONE AT THE FACTORY. PIPE TAPS MAY BE DONE ON SITE USING A TAPPING MACHINE BY AN EXPERIENCED OPERATOR. ALL TAPS ARE SUBJECT TO OWNER APPROVAL AND ANY REJECTED MATERIALS SHALL BE REPLACED AT THE CONTRACTOR'S EXPENSE. TAPPED DI PIPE SHALL BE CLASS 53 MINIMUM. DIRECT TAPS ON PIPE ARE TO BE LOCATED SUCH THAT ADJACENT FITTING BOLTS OR SHACKLE RODS DO NOT INTERFERE WITH INSTALLATION OF GAUGES, SWITCHES OR AIR VALVES. TAPPED PIPE WILL BE REJECTED IF EQUIPMENT CANNOT BE INSTALLED CLEANLY AND DISASSEMBLED EASILY.
11. MINOR MECHANICAL PIPING: ALL VALVES 2" AND LARGER SHALL INCLUDE HANDWHEEL OPERATORS. ALL BALL VALVES SMALLER THAN 2" SHALL HAVE 1/4 TURN FULL HANDLES AND BE RATED FOR 300psi WORKING PRESSURE.
12. PLUMB ALL CONTROL VALVE PILOT DRAINS, AIR VALVE OUTLETS, AND PUMP HEAD DRAINS TO FLOOR DRAINS USING COPPER AND COMPRESSION FITTINGS OR SCH 40 PVC PIPE AND FITTINGS. SECURE TO PIPE RUNS OR SUPPORTS AWAY FROM TRAVELED PATHS. PROVIDE UNIONS OR COUPLINGS AS NECESSARY TO ALLOW COMPLETE DISASSEMBLY. MAINTAIN CONTINUOUS DRAINING GRADE ON PIPE RUNS.
13. CONTRACTOR SHALL PROVIDE ALL NECESSARY THRUST RESTRAINT, INCLUDING BUT NOT LIMITED TO CONCRETE BLOCKING, SHACKLE RODS MECHANICAL THRUST RESTRAINT (MEGALUGS OR EQUAL) AND TRUE RESTRAINED JOINT PIPE (TRJ) PIPE.
14. IN THE EVENT THAT A SECTION OF PIPING FAILS A PRESSURE TEST, AND ANY MECHANICAL JOINTS WITH MEGA-LUG STYLE RESTRAINTS NEED TO BE DISASSEMBLED, THE MEGA-LUGS AND THE ASSOCIATED PIPE MAY NOT BE REUSED AND MUST BE REPLACED AT THE CONTRACTOR'S EXPENSE.
15. CONTRACTOR SHALL PROVIDE INSULATING FLANGE KITS OR TRANSITION COUPLINGS BETWEEN ALL DISSIMILAR PIPING MATERIALS.
16. ALL FLOW METERS SHALL BE INSTALLED SO THAT THERE IS A MINIMUM STRAIGHT RUN LENGTH OF 5 PIPE DIAMETERS UPSTREAM AND 2 PIPE DIAMETERS DOWNSTREAM.
17. ALL PVC FITTINGS SHALL BE SOCKET END-TYPE FITTINGS UNLESS OTHERWISE NOTED.
18. ALL BUTTERFLY VALVES (BFV) SHALL BE FULL LUG WAFER STYLE, UNLESS OTHERWISE NOTED.
19. ALL VALVES SHALL BE REMOVABLE WITHOUT HAVING TO CUT PIPE.
20. FLANGE COUPLING ADAPTERS (FCA), RESTRAINED FLANGE COUPLING ADAPTERS (RFCA), AND COUPLINGS SHALL BE EQUAL TO ROMAC.
21. ALL PRESSURE PIPE SHALL HAVE RESTRAINED JOINTS. EXPOSED PIPING SHALL BE FLANGED OR GROOVED; BURIED PIPING SHALL BE MECHANICALLY RESTRAINED JOINTS. PUSH ON JOINTS WITH FIELD LOK (OR APPROVED EQUAL) ARE ACCEPTABLE RESTRAINED JOINT IN STRAIGHT SECTIONS WITH BLOCKING OR RESTRAINED FITTINGS AS SPECIFIED. PROVIDE TRUE (BOLTLESS) RESTRAINED JOINT PIPE AND CONCRETE BLOCKING WHERE SPECIFIED ON PLANS.
22. PIPING WHICH NORMALLY OPERATES UNDER FULL CONDITIONS WITH HYDROSTATIC HEAD HIGHER THAN THE CROWN OF THE PIPE SHALL BE CONSIDERED PRESSURE PIPING. PIPING WHICH NORMALLY OPERATES AT A HYDROSTATIC HEAD NO HIGHER THAN THE PIPE CROWN SHALL BE CONSIDERED GRAVITY PIPELINES. ALL PIPING SHALL BE HYDROSTATICALLY TESTED AND DISINFECTED (WHERE APPLICABLE) IN ACCORDANCE WITH THE GUIDELINES IDENTIFIED IN THE SPECIFICATIONS.
23. UNLESS OTHERWISE NOTED, PIPE MATERIAL SHALL BE USED BASED ON PIPE FUNCTION AND AS SPECIFIED IN THE PIPE SCHEDULE (SEE SPECIFICATIONS). PREPARE AND COAT ALL EXPOSED PIPING PER THE FINISHES SECTION OF THE SPECIFICATIONS.
24. ALL PIPE PENETRATIONS SHALL BE SEALED WATERTIGHT.
25. HEAT TRACE AND INSULATE ALL ABOVE GRADE, EXPOSED WATER AND FLUID PROCESS PIPES TO 3' BELOW GRADE.
26. COPPER PIPING MAY BE USED IN LIEU OF SCH 40 PVC FOR PLUMBING WATER SUPPLY LINES.
27. ABS MAY BE USED IN LIEU OF SCH 40 PVC FOR PLUMBING DRAIN, WASTE, VENT LINES.

## MAJOR MECHANICAL LEGEND

PIPE AND PIPE JOINING (PLAN VIEW)				PIPE SUPPORTS (PLAN VIEW)	
FL x FL	FL x =TRJ	FL x PE	FL x GR	PIPE SPOOL	▲ STAND-ON/CONCRETE
					OTHER PIPING SYMBOLS
					← PIPE FLOW ARROW (COLOR BY PIPE FUNCTION)
					
					
					
					
FITTINGS (PLAN VIEW)					
FLANGED	MECHANICAL	GROOVED	SOCKET		
				90° BEND/ELBOW	
				45° BEND/ELBOW	
				22 1/2° BEND/ELBOW	
				11 1/2° BEND/ELBOW	
				REDUCER	
				CROSS	
				TEE	
				WYE	
VALVES AND METERS (PLAN VIEW)					
	ECCENTRIC (PLUG) VALVE, FULL PORT			BUTTERFLY VALVE (W/ HANDWHEEL AND WAFER W/ LEVER SHOWN)	
	GATE VALVE			ELECTROMAGNETIC FLOWMETER	


## GENERAL PIPE SUPPORT NOTES

TABLE A: PIPE SUPPORT DESIGN CRITERIA		
PIPE SIZE	ROD SIZE	DUCTILE IRON MAX. SPAN FOR PIPE SUPPORTS (FT)
8"	7/8"	10
10"	7/8"	10
12"	7/8"	10
24"	1-1/2"	10

1. FOR PIPE SIZES THAT ARE NOT LISTED IN ABOVE TABLE, THE NEXT LARGER PIPE SIZE SHALL BE USED FOR DETERMINING LOADING AND SUPPORT SPACING.
2. ROD SIZE IS BASED ON CARRYING SINGLE PIPE. WHEN MORE THAN ONE PIPE IS TO BE SUPPORTED, RODS SHALL BE SIZED USING SUM OF DESIGN WEIGHTS TO DETERMINE TOTAL LOAD.
3. INSTALL AT LEAST ONE HANGER PER PIPE LENGTH. LOCATE AS NEAR THE END CONNECTION AS POSSIBLE.
4. PROVIDE TURNBUCKLE WITH SUPPORT ROD FOR PIPES SUBJECT TO HORIZONTAL MOVEMENT.
5. PROVIDE LATERAL AND SEISMIC BRACING AS SPECIFIED & REQUIRED.
6. ALL CONNECTIONS TO CONCRETE SHALL BE CONCRETE ANCHORS PER SPECIFICATIONS & STRUCTURAL DETAILS.
7. MSS REFERS TO MANUFACTURERS STANDARDIZATION SOCIETY OF THE VALVE AND FITTING INDUSTRY, STANDARD PRACTICE SP 58 AND SP 69.
8. IF SUPPORT IS SUBMERGED OR LOCATED BELOW THE TOP OF THE WALL WITHIN A WATER BEARING STRUCTURE, ALL HARDWARE AND SUPPORT MATERIAL SHALL BE STAINLESS STEEL. IN ALL OTHER AREAS, MATERIALS SHALL BE HOT-DIP GALVANIZED UNLESS NOTED OTHERWISE.
9. CONTRACTOR SHALL PROVIDE ALL NECESSARY EQUIPMENT, MATERIALS, AND LABOR FOR CONSTRUCTING PIPE SUPPORT SYSTEMS.
10. PIPE SUPPORT SYSTEMS AS DETAILED PROVIDE GENERAL GUIDELINES FOR HOW PIPES SHALL BE SUPPORTED. ADDITIONAL SUPPORT CONFIGURATIONS MAY BE REQUIRED. CONTRACTOR SHALL SUBMIT ALTERNATE SUPPORT DETAILS FOR APPROVAL.
11. CONTRACTOR SHALL PROVIDE SUPPORTS AS NEEDED TO SECURE PIPING SYSTEM IN NORMAL AND TEST OPERATING CONDITIONS.
12. CONTRACTOR IS RESPONSIBLE FOR DESIGN OF PIPE SUPPORTS, HANGERS AND SEISMIC BRACING. SEE SPECIFICATIONS FOR ADDITIONAL INFORMATION.

**CALL 48 HOURS BEFORE YOU DIG**  
**1-800-424-5555 (811)**  
UNDERGROUND SERVICE

  
**RH2 ENGINEERING**  
 40 YEARS SINCE 1978  
 BOTHELL, WA  
 22722 29th Drive SE, Suite 210  
 www.rh2.com 1.800.720.8052





**CITY OF LYNNWOOD**  
**LIFT STATION 8 IMPROVEMENTS**  
**LYNNWOOD WASHINGTON**

**MECHANICAL GENERAL NOTES AND DETAILS**

ENGINEER: BMS	DATE: Mar 26, 2019	JOB NO.: 117-288					
REVIEWED: RJF	DATE: Mar 26, 2019	CLIENT: LYNN	FILENAME: LSR-D-MEC03.DWG				
<b>REVISIONS</b>							
	03/27/19	ISSUED FOR BIDDING	R/JF	OMP	BY	REVIEW	DATE
NO.	DATE	DESCRIPTION	BY	BY	BY	BY	DATE
SCALE: SHOWN							
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"							
DWG NO.: M01	SHEET NO.: 23						



CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE



NO.	SIZE (WxH)	OPERATING HEAD	DESCRIPTION	GATE TYPE	FRAME TYPE	ACTUATOR TYPE
SG1	18" X 18"	20 FT	SLIDE	SC, NRS, SST, UPO	FLG	NUT
SG2	18" X 18"	20 FT	SLIDE	SC, NRS, SST, UPO	FLG	NUT
SG3	24" X 24"	20 FT	SLIDE	SC, NRS, SST, UPO	FLG	NUT

**SLIDE GATE NOTES:**  
GATE AND FRAME SHALL BE GOLDEN HARVEST OR EQUAL. GATE FRAME, STEM AND NUT ACTUATOR TO BE PROVIDED BY GATE MANUFACTURER. INSTALL PER MANUFACTURER'S RECOMMENDATIONS


NO.	PUMP TYPE	HP	FLOW	HEAD	DISCHARGE SIZE
P201	HIDROSTAL F4K-S	64.3	1,000 gpm	140 FT	4"
P202	HIDROSTAL F4K-S	64.3	1,000 gpm	140 FT	4"
P203	HIDROSTAL F4K-S	64.3	1,000 gpm	140 FT	4"
P204	HIDROSTAL F4K-S	64.3	1,000 gpm	140 FT	4"

**ABBREVIATIONS**


UPO	UPWARD OPENING
SST	STAINLESS STEEL
SC	SELF CONTAINED
NRS	NON RISING STEM

**MECHANICAL NOTES:**  
1. WHERE A DESCRIPTION OF EQUIPMENT, ETC. IS CALLED OUT ON THIS DRAWING, IT IS THE INTENT THAT THAT MAKE AND MODEL IS THE STANDARD FOR THIS PROJECT, AND THERE IS AN IMPLIED 'OR EQUAL' ATTACHED TO THE DESCRIPTION.

**PROPOSED LIFT STATION 8 MECHANICAL PLAN**  
1/4" = 1'-0"



**PUMP STATION OBLIQUE**  
NOT TO SCALE







**PUMP STATION OBLIQUE**  
NOT TO SCALE

CITY OF LYNNWOOD  
LIFT STATION 8 IMPROVEMENTS  
LYNNWOOD WASHINGTON  
**EXISTING AND PROPOSED MECHANICAL PLAN**

NO.	DATE	DESCRIPTION	BY	REVIEW
1	03/27/19	ISSUED FOR BIDDING	OMP	RJF



CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE





CITY OF LYNNWOOD  
LIFT STATION 8 IMPROVEMENTS  
MECHANICAL SECTIONS AND DETAILS I

NO.	DATE	DESCRIPTION	BY	REVIEW
03/27/19		ISSUED FOR BIDDING		




CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE



**MODIFIED EXISTING WET WELL SECTION**



1/2" = 1'-0"

C  
M02



**FLOW METER MANHOLE PLAN**


1/2" = 1'-0"



**FLOW METER MANHOLE SECTION**



1/2" = 1'-0"

300  
M02



**PUMPING PORT/PIGGING STATION PLAN**

1/2" = 1'-0"



**PUMPING PORT/PIGGING STATION SECTION**






1/2" = 1'-0"

A  
M04

CITY OF LYNNWOOD  
LIFT STATION 8 IMPROVEMENTS  
MECHANICAL SECTIONS AND DETAILS II

ENGINEER	DATE	REVISIONS	NO.	DATE	DESCRIPTION
REVIEWED: R/JF	03/27/19	ISSUED FOR BIDDING			
DESIGNED: L/YN					
CHECKED: R/JF					
DATE: Mar 26, 2019					
CLIENT: LYNN					
JOB NO.: 117-288					
FILENAME: LSS-D-MEC01.DWG					
PLOT DATE: Mar 26, 2019					









**ACCESS HATCH SAFETY CHAIN DETAILS** (301 TYP.)  
NOT TO SCALE

**ISOLATION VALVE DETAIL** (304 TYP.)  
NOT TO SCALE

**PIPE SUPPORT** (308 TYP.)  
NOT TO SCALE



**MECHANICAL SEAL PIPE PENETRATION** (309 TYP.)  
NOT TO SCALE



**PRESSURE GAUGE** (306 TYP.)  
NOT TO SCALE

**RH2 ENGINEERING**  
40 YEARS SINCE 1978  
BOTHELL, WA  
22722 29th Drive SE, Suite 210  
www.rh2.com 1.800.720.8052

CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE

**PROFESSIONAL ENGINEER**  
SIGNED: 03/27/19

**CITY OF LYNNWOOD**  
LIFT STATION 8 IMPROVEMENTS  
MECHANICAL DETAILS

**REVISIONS**

NO.	DATE	DESCRIPTION	BY	REVIEW
1	03/27/19	ISSUED FOR BIDDING	RJF	

SCALE: SHOWN  
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"  
DWG NO.: M05 SHEET NO.: 27 OF 48



ONE-LINE DIAGRAM SYMBOLS	
	CIRCUIT BREAKER XXX/YY - CB SIZE & NO. OF POLES ET - ELECTRONIC TRIP TM - THERMAL MAGNETIC BREAKER MCP - MOTOR CIRCUIT PROTECTOR SE - SERVICE ENTRANCE GFI - GROUND FAULT INTERRUPTER
	FUSE
	FUSED DISCONNECT SWITCH
	PLUG-IN CONNECTION
	RTM RUN TIME METER
	OC MOTOR OPERATION COUNTER
	SSRVs REDUCED VOLTAGE STARTER
	VARIABLE FREQUENCY DRIVE
	MOTOR STARTER
	MOTOR STARTER W/ OPERATOR DEVICES A - HAND-OFF-AUTO B - OPERATIONAL COUNTER C - RUN TIME METER D - RUN LIGHT E - FAIL LIGHT F - EMERGENCY STOP
	KIRK KEY INTERLOCK
	POWER TRANSFORMER
	CONTROL POWER TRANSFORMER
	TRANSFORMER
	CURRENT TRANSFORMER
	VOLTAGE TRANSFORMER
	CONTACTOR
	CAPACITOR
	ENGINE GENERATOR
	GENERATOR CONNECTION RECEPTACLE
	SOLID NEUTRAL
	TERMINAL BLOCK
	SURGE PROTECTION DEVICE
	SURGE PROTECTION DEVICE (ALTERNATIVE)

GROUNDING SYSTEM SYMBOLS	
	GROUND
	METAL PIPE GROUND
	CONNECTION POINT, EXOTHERMIC WELD, CADWELD OR APPROVED EQUAL
	GROUND ROD SIZED PER N.E.C. USE EXOTHERMIC WELD CONNECTION AT THE GROUND ROD.
	PIGTAIL, BARE COPPER, LENGTH AS REQUIRED, 8" MINIMUM.
	CONNECTION POINT, MECHANICAL, COMPRESSION TYPE.

ELECTRICAL SITE PLAN SYMBOLS	
	UTILITY POLE AND GUY WIRE
	MANHOLE OR HANDHOLE
	BURIED POWER VAULT OR MANHOLE
	TELEPHONE VAULT OR PEDESTAL
	FIBER OPTICS VAULT OR PEDESTAL
	LUMINAIRE
	PAD-MOUNT TRANSFORMER

PANELBOARDS, SWITCHES, AND EQUIPMENT	
	SERVICE ENTRANCE, SWITCHGEAR, MOTOR CONTROL CENTER, OR PANELBOARD
	SURFACE MOUNTED PANELBOARD
	FLUSHED MOUNTED PANELBOARD
	FIELD CONTROL STATION WITH NEMA REQUIREMENTS. N1 - NEMA 1 N3R - NEMA 3R N4 - NEMA 4 N4SS - NEMA 4 STAINLESS STEEL N4F - NEMA 4 FIBERGLASS N6 - NEMA 6 N12 - NEMA 12 GASKETED

	EQUIPMENT MOUNTING STAND
	HEATER, WATTAGE NOTED
	EQUIPMENT CONNECTION
	SINGLE PHASE MOTOR. HORSEPOWER AS NOTED
	THREE PHASE MOTOR. HORSEPOWER AS NOTED
	SINGLE PHASE MOTOR. HORSEPOWER AS NOTED
	ELECTRICAL PLUG
	DISCONNECT SWITCH
	FUSED DISCONNECT SWITCH
	COMBINATION MOTOR STARTER AND DISCONNECT SWITCH

RECEPTACLES AND JUNCTION BOX SYMBOLS	
	CEILING JUNCTION BOX
	WALL JUNCTION BOX
	FLOOR JUNCTION BOX
	DUPLIX WALL RECEPTACLE, 120V WP = WEATHERPROOF G = GROUNDED IG = ISOLATED GROUND GFI = GROUND FAULT INTERRUPTER
	DOUBLE DUPLIX
	SINGLE RECEPTACLE, 120V
	SINGLE RECEPTACLE, 208V
	DUPLIX FLOOR RECEPTACLE, 120V
	SPECIAL PURPOSE WALL RECEPTACLE, RATING AS NOTED
	CLOCK
	TELEVISION
	TELEPHONE
	TELEPHONE/DATA WITH CABLE
	TELEPHONE/DATA WITHOUT CABLE

SWITCH OUTLETS	
	STANDARD SWITCH, 120VAC, 20 AMP
	3-WAY SWITCH, 120VAC, 20 AMP
	3-POSITION SWITCH, 120VAC, 20 AMP, LABEL SWITCH POSITION
	HAND-OFF-MOTION OR PHOTO
	SINGLE-POLE
	DOUBLE-POLE
	THREE WAY
	FOUR WAY
	DIMMER
	PILOT-LIGHTED
	KEY-OPERATED
	LOW VOLTAGE
	MASTER
	PUSHBUTTON

LIGHTING FIXTURES/DEVICES	
	FLUORESCENT FIXTURE
	WALL/CEILING MOUNTED FIXTURE
	EMERGENCY LIGHT WITH SELF CONTAINED BATTERY
	SURFACE OR PENDANT MOUNTED FIXTURE
	RECESSED FIXTURE
	MOTION DETECTOR
	PHOTO CONTROL CELL

FIRE SYSTEM SYMBOLS	
	HEAT DETECTOR
	SMOKE DETECTOR
	FIRE ALARM DISPATCH STROBE ALARM
	FIRE ALARM AUDIBLE/VISUAL ALARM
	FIRE ALARM MANUAL PULL STATION

ADDITIONAL SYMBOLS	
	SOUND SYSTEM SPEAKER
	SOUND SYSTEM VOLUME CONTROL
	DOORBELL

VALVE SYMBOLS	
	PILOT VALVE SOLENOID
	VALVE
	CHECK VALVE
	CONTROL VALVE

PID FORMAT	
	SUPERSCRIPT
	INSTRUMENT BUBBLE
X	X=MEASURED OR INITIATING VARIABLE
Y	Y=READOUT OR FUNCTION
Z	Z=MODIFIER
ABC	ABC=LOOP NUMBER

ISA STANDARDS FOR P&ID			
1st LETTER (MEASURED OR INITIATING VARIABLE)	2nd LETTER (READOUT OR FUNCTION)	3rd LETTER (MODIFIER)	
A	ANALYSIS		
B	BURNER (BATTERY)	ALARM	(BACK) CLOSED
C	COMMUNICATION	CONTROL (DELAY)	
D	DENSITY		
E	VOLTAGE		
F	FLOW		FAIL (FLOW) GREEN BULB HIGH
G	GAS		
H	HAND	MANUAL INDICATE	
I	CURRENT (INTRUSION)		
J	POWER (EQUIPMENT)		
K	TIME LEVEL	CONTROL STATION LIGHT	
L			LOW MIDDLE
M	MOTION		
N	USERS CHOICE		
O	USERS CHOICE		OPEN
P	PRESSURE	(PUMP)	(PRESSURE)
Q	QUANTITY (EVENT)	TOTALIZE RECORD SWITCH TRANSMITTER	RED BULB SOLENOID (TRANSMITTER)
R	RADIATION (REQ'D)		
S	SPEED (SMOKE)		
T	TEMPERATURE		
U	MULTI VARIABLE	MULTI FUNCTION VALVE	
V	VISCOSITY (pH)		
W	WEIGHT		
X	UNCLASSIFIED	RELAY (TRANSDUCER)	
Y	USERS CHOICE		
Z	POSITION		

ABBREVIATIONS	
SPDT	SINGLE POLE, DOUBLE THROW
SPST	SINGLE POLE, SINGLE THROW
DPST	DOUBLE POLE, SINGLE THROW
WP	WEATHER-PROOF
GFI	GROUND FAULT INTERRUPTER
P	POWER
C	CONTROL
J	INSTRUMENTATION
PC	POWER & CONTROL
CJ	CONTROL & INSTRUMENTATION
CKT.	CIRCUIT
C.O.	CONDUIT ONLY
N.L.	NIGHT LIGHT
AL	ALUMINUM
CU	COPPER

INDICATE TYPE BY LETTER		INSTRUMENT METER	
V	VOLTMETER	A	AMMETER
AH	AMPERE-HOUR	VAR	VARMETER
		VARH	VARHOUR METER
		PF	POWER FACTOR
		V	VOLTMETER
		VA	VOLT AMMETER
		W	WATTMETER
		WH	WATTHOUR METER

RACEWAY LEGEND	
	PROPOSED POWER
	PROPOSED TELEPHONE
	PROPOSED INSTRUMENTATION
	PROPOSED FIBER OPTICS

BUILDING OR FACILITY PLAN LEGEND	
	480 VOLT EXPOSED RACEWAY
	480 VOLT WIRING CONCEALED, UNDERGROUND, EMBEDDED, OR CONCRETE ENCASED RACEWAY
	120/208/240 VOLT EXPOSED RACEWAY
	120/208/240V WIRING CONCEALED, UNDERGROUND, EMBEDDED, OR CONCRETE ENCASED RACEWAY
	CONTROL OR INSTRUMENTATION EXPOSED RACEWAY
	CONTROL OR INSTRUMENTATION, UNDERGROUND, EMBEDDED, OR CONCRETE ENCASED RACEWAY
	HOME RUN TO PANELBOARD OR AS INDICATED
	CONDUIT RUN, BROKEN AND CONTINUED SAME SHEET OR AS NOTED
	FLEXIBLE CONDUIT
	CONDUIT RUN. HATCH MARKS INDICATE NUMBER OF CONDUCTORS
	CALLOUT INDICATING CONDUIT SIZE, NUMBER AND SIZE OF WIRE.
	CALLOUT INDICATING CONDUIT PER SCHEDULE
	CONDUIT BENT UP OR TOWARD
	CONDUIT BENT DOWN OR AWAY
	CAPPED CONDUIT

P&ID BUBBLE IDENTIFICATION CHART	
EXISTING	FUNCTION
	INSTRUMENT IDENTIFICATION BUBBLE
	FIELD MOUNTED DEVICE OR INSTRUMENT
	FRONT PANEL MOUNTED INSTRUMENT OR DEVICE (LOCAL PANEL)
	BACK PANEL MOUNTED INSTRUMENT OR DEVICE (LOCAL PANEL)
	FRONT PANEL MOUNTED INSTRUMENT OR DEVICE (LAB ROOM PANEL)
	OPERATOR INTERFACE DISPLAY (LOCAL PANEL)
	OPERATOR INTERFACE DISPLAY (LAB ROOM PANEL)

LADDER LOGIC SYMBOL LEGEND			
	INDICATOR LIGHT		RELAY TR - TIMED RELAY CR - CONTROL RELAY
	LIMIT SWITCH, NORMALLY OPEN		FLOAT SWITCH, NORMALLY OPEN
	LIMIT SWITCH, NORMALLY CLOSED		FLOAT SWITCH, NORMALLY CLOSED
	TIME DELAY CONTACT, NORMALLY OPEN, TIME TO CLOSE		PUSHBUTTON, NORMALLY CLOSED
	TIME DELAY CONTACT, NORMALLY CLOSED, TIME TO OPEN		PUSHBUTTON, NORMALLY OPEN
	TIME DELAY CONTACT, NORMALLY OPEN, TIME TO OPEN		THERMOSTAT, THERMO SWITCH, NORMALLY OPEN
	TIME DELAY CONTACT, NORMALLY CLOSED, TIME TO CLOSE		THERMOSTAT, THERMO SWITCH, NORMALLY CLOSED
	RELAY CONTACT, NC		FLOWSWITCH, NORMALLY OPEN
	RELAY CONTACT, NO		FLOWSWITCH, NORMALLY CLOSED
	PRESSURE SWITCH, NORMALLY OPEN		2 POLE SWITCH
	PRESSURE SWITCH, NORMALLY CLOSED		3 POLE SWITCH
LADDER LOGIC LINETYPES			
	COMPONENT INSTALLED INSIDE ENCLOSURE		
	COMPONENT INSTALLED ON FRONT OF ENCLOSURE		
	FIELD CONNECTED COMPONENT		

P&ID BUBBLE IDENTIFICATION CHART	
EXISTING	FUNCTION
	INSTRUMENT IDENTIFICATION BUBBLE
	FIELD MOUNTED DEVICE OR INSTRUMENT
	FRONT PANEL MOUNTED INSTRUMENT OR DEVICE (LOCAL PANEL)
	BACK PANEL MOUNTED INSTRUMENT OR DEVICE (LOCAL PANEL)
	FRONT PANEL MOUNTED INSTRUMENT OR DEVICE (LAB ROOM PANEL)
	OPERATOR INTERFACE DISPLAY (LOCAL PANEL)
	OPERATOR INTERFACE DISPLAY (LAB ROOM PANEL)

GENERAL NOTES	
1. THIS IS A STANDARD LEGEND. NOT ALL OF THE INFORMATION SHOWN ON THIS PAGE WILL APPEAR IN THIS SET OF PLANS.	
2. THESE DRAWINGS ARE DIAGRAMMATIC ONLY; EXACT LOCATIONS OF ELECTRICAL EQUIPMENT SHALL BE DETERMINED IN THE FIELD BY THE CONTRACTOR. THE INSTALLATION OF ALL EQUIPMENT SHOWN ON THESE DRAWINGS OR DESCRIBED IN THE SPECIFICATIONS SHALL CONFORM TO THE REQUIREMENTS SET FORTH IN THE LATEST EDITIONS OF ALL APPLICABLE CODES AND UTILITY COMPANY STANDARDS. CONTACT THE UTILITY COMPANY REPRESENTATIVES AND VERIFY THEIR REQUIREMENTS.	
3. NOTIFY THE ENGINEER IMMEDIATELY IF CONFLICTS IN EQUIPMENT LOCATIONS ARE DISCOVERED OR IF PROBLEMS ARISE DUE TO FIELD CONDITIONS, LACK OF INFORMATION OR ANY OTHER REASON. NO PAYMENT WILL BE MADE FOR CHANGES WHICH HAVE NOT BEEN REVIEWED BY THE ENGINEER.	

CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE

**RH2**  
ENGINEERING  
40 YEARS  
SINCE 1978  
BOTHELL, WA  
22722 29th Drive SE, Suite 210  
www.rh2.com  
1.800.720.8052

STATE OF WASHINGTON  
PROFESSIONAL ENGINEER  
MICHAEL J. BERRY  
45317  
SIGNED: 03/27/19




STATE OF WASHINGTON  
PROFESSIONAL ENGINEER  
MICHAEL J. BERRY  
45317  
SIGNED: 03/27/19

CITY OF LYNNWOOD  
LIFT STATION 8 IMPROVEMENTS  
ELECTRICAL LEGEND  
LYNNWOOD WASHINGTON


ENGINEER: KMS	DATE: Mar 25, 2019	CLIENT: LYNN	JOB NO.: 117-288	FILENAME: LSR-D-ELEC01.DWG
REVIEWED: CMR	DATE: Mar 26, 2019			
ISSUED FOR BIDDING	03/27/19			
NO.	DATE	DESCRIPTION	BY	REVIEW
SCALE: SHOWN				
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"				
DWG NO.: E01	SHEET NO.: 28			



CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE



**GROUNDING**  
NO SCALE



**GENERATOR & TRANSFER SWITCH CONNECTION DIAGRAM**  
NO SCALE

**ONE-LINE DIAGRAM**  
NOT TO SCALE

LOAD CALCULATIONS	
PUMP 1 (65 HP)	81.0A X 1.25 = 101.3 AMPS
PUMP 2 (65 HP)	81.0A X 1.00 = 81.0 AMPS
PUMP 3 (65 HP)	81.0A X 1.00 = 81.0 AMPS
PUMP 4 (65 HP)	81.0A X 1.00 = 81.0 AMPS
LIGHTING TRANSFORMER (15 kVA)	18.1A X 1.00 = 18.1 AMPS
<b>TOTAL</b>	<b>362.4 AMPS</b>

- ELECTRICAL NOTES**
1. PROPOSED UTILITY METERING. METER BASE AND ENCLOSURE BY CONTRACTOR PER SERVING UTILITY REQUIREMENTS. METER BY SNOHOMISH COUNTY PUD.
  2. PROPOSED NEMA 3R CURRENT TRANSFORMER ENCLOSURE PER UTILITY REQUIREMENTS.
  3. PROPOSED FUSING OR CIRCUIT BREAKER PER SURGE PROTECTION DEVICE MANUFACTURER'S RECOMMENDATION.
  4. GROUND ROD PER N.E.C. (TYPICAL). SEE DWG NO. E11 FOR DETAIL.
  5. SEE DWG NO. E12 FOR CONDUIT AND CONDUCTOR SCHEDULE.
  6. SEE DWG NO. E12 FOR ELECTRICAL EQUIPMENT SCHEDULE.


CITY OF LYNNWOOD  
LIFT STATION 8 IMPROVEMENTS  
ONE-LINE DIAGRAM  
LYNNWOOD WASHINGTON

REVISIONS	DATE	DESCRIPTION	BY	REVIEW
1	03/27/19	ISSUED FOR BIDDING	OMP	RUF

SCALE: SHOWN  
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"  
DWG NO. E02 SHEET NO. 29 48




CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE



SIGNED: 03/27/19



SIGNED: 03/27/19



**ELECTRICAL SITE PLAN**  
1" = 10'



ELECTRICAL NOTES	
(XX)	1. SEE DWG NO. E12 FOR CONDUIT AND CONDUCTOR SCHEDULE.
(X)	2. SEE DWG NO. E12 FOR ELECTRICAL EQUIPMENT SCHEDULE.
	3. SEE DWG NO. E04 FOR UNDERGROUND CONDUITS BETWEEN ELECTRICAL SHELTER, GENERATOR, WET WELLS, AND VAULTS.
	4. CONTRACTOR SHALL COORDINATE SECONDARY POWER REQUIREMENTS WITH SNOHOMISH COUNTY PUD. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL WORK NOT PERFORMED BY PUD.
5	5. PROPOSED POLE MOUNTED TRANSFORMERS BY SNOHOMISH COUNTY PUD INSTALLED ON EXISTING POLE.
6	6. PROPOSED UNDERGROUND SECONDARY POWER SERVICE TO POWER HAND HOLE. CONTRACTOR SHALL PROVIDE AND INSTALL 6" PVC CONDUIT FROM POWER HAND HOLE TO EXISTING UTILITY POLE. USING A 60" RADIUS STEEL ELBOW TO TERMINATE THE CONDUIT AT LEAST 6" FROM THE POLE. SNOHOMISH COUNTY PUD SHALL PROVIDE AND INSTALL SECONDARY SERVICE CONDUCTORS TO POWER HAND HOLE.
7	7. PROPOSED POWER HAND HOLE. CONTRACTOR SHALL PROVIDE EXCAVATION AND RESTORATION FOR POWER HAND HOLE. CONTRACTOR SHALL PROVIDE AND INSTALL POWER HAND HOLE PER SNOHOMISH COUNTY PUD REQUIREMENTS.
8	8. SEE FIBER OPTIC CONNECTION PLAN FOR CONTINUATION, THIS SHEET.
9	9. SEE ELECTRICAL SITE PLAN FOR CONTINUATION, THIS SHEET.
10	10. SEE APPENDIX FOR FIBER OPTIC CONNECTION LOCATION. CONTRACTOR SHALL CONNECT PROPOSED FIBER OPTIC CABLE TO EXISTING CITY FIBER OPTIC NETWORK AT EACH LOCATION.




**FIBER OPTIC CONNECTION PLAN**  
1" = 250'

CITY OF LYNNWOOD  
LIFT STATION 8 IMPROVEMENTS  
ELECTRICAL SITE PLAN



ENGINEER	DATE	REVISIONS	NO.	DATE	DESCRIPTION	BY	REVIEW
RMS	03/27/19	ISSUED FOR BIDDING	1				
CMR							





CALL 48 HOURS BEFORE YOU DIG  
 1-800-424-5555 (811)  
 UNDERGROUND SERVICE

**RH2**  
 ENGINEERING  
 40 YEARS SINCE 1978  
 BOTTHELL, WA  
 22722 29th Drive SE, Suite 210  
 www.rh2.com 1.800.720.8052

**RICHARD BALDWIN**  
 STATE OF WASHINGTON  
 32878  
 REGISTERED PROFESSIONAL ENGINEER  
 SIGNED: 03/27/19

**WALTER MICHAEL BERRY**  
 STATE OF WASHINGTON  
 45317  
 REGISTERED PROFESSIONAL ENGINEER  
 SIGNED: 03/27/19

CITY OF LYNNWOOD  
 LIFT STATION 8 IMPROVEMENTS  
 LYNNWOOD WASHINGTON  
**POWER DISTRIBUTION & SIGNAL PLAN**

NO.	DATE	DESCRIPTION	BY	REVIEW
1	03/27/19	ISSUED FOR BIDDING	OMP	R/J

SCALE: SHOWN  
 DRAWING IS FULL SCALE WHEN BAR MEASURES 2"  
 DWG NO.: E04 SHEET NO.: 31 48


- ELECTRICAL NOTES**
1. SEE ELECTRICAL SITE PLAN DWG NO. E03 FOR CONTINUATION.
  2. GROUND ROD PER N.E.C. (TYPICAL). USE EXOTHERMIC WELD CONNECTION AT THE GROUND ROD. SEE DWG NO. E11 FOR DETAIL. LOCATE GROUND RODS 2' MINIMUM FROM CONCRETE PAD.
  3. CONNECTION TO REINFORCEMENT GRID (TYPICAL OF 2 LOCATIONS). SEE DWG NO. E11 FOR ADDITIONAL DETAIL.
  4. CONNECTION TO SHELTER STRUCTURAL STEEL.
  5. NOT ALL ELECTRICAL SHELTER CONDUITS SHOWN. SEE ELECTRICAL SHELTER DETAILS DWG NO. E05 FOR ADDITIONAL CONDUITS.
  6. SEE DWG NO. E12 FOR CONDUIT AND CONDUCTOR SCHEDULE.
  7. SEE DWG NO. E12 FOR ELECTRICAL EQUIPMENT SCHEDULE.
  8. SEE DWG NO. E12 FOR LIGHTING SCHEDULE.

SHELTER ROOF AND LIGHTING NOT SHOWN THIS VIEW FOR CLARITY. SEE ELECTRICAL SHELTER DETAILS DWG NO. E05 FOR MORE INFORMATION.

**POWER DISTRIBUTION AND SIGNAL PLAN**  
 1/4" = 1'-0"








ELECTRICAL SHELTER  
CONCRETE PAD


SHELTER ROOF, ROOF SUPPORTS,  
AND LIGHTING NOT SHOWN THIS  
VIEW FOR CLARITY

### ELECTRICAL SHELTER PLAN

3/4" = 1'-0"



ELECTRICAL NOTES	
(XX)	1. SEE DWG NO. E12 FOR CONDUIT AND CONDUCTOR SCHEDULE.
(X)	2. SEE DWG NO. E12 FOR ELECTRICAL EQUIPMENT SCHEDULE.
A#	3. SEE DWG NO. E12 FOR LIGHTING SCHEDULE.



### ELECTRICAL SHELTER FRONT ELEVATION

3/4" = 1'-0"

CALL 48 HOURS  
BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE

**RH2**  
ENGINEERING  
40 YEARS  
SINCE 1978  
BOTHELL, WA  
22722 29th Drive SE, Suite 210  
www.rh2.com  
1.800.720.8052



SIGNED: 03/27/19



SIGNED: 03/27/19

CITY OF LYNNWOOD  
LIFT STATION 8  
IMPROVEMENTS  
LYNNWOOD  
WASHINGTON


### ELECTRICAL SHELTER DETAILS

ENGINEER	DATE	REVISIONS	ISSUED FOR BIDDING	DATE	DESCRIPTION	BY	REVIEW
KMS	Mar 25, 2019						
CMR	Mar 26, 2019						
	03/27/19		ISSUED FOR BIDDING				

SCALE: SHOWN	
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"	
DWG NO.: E05	SHEET NO.: 32
	48



PROPOSED MOTOR CONTROL CENTER "MCC" WITH DEPTH EQUAL TO 30"




CONCRETE SHELTER PAD

**MOTOR CONTROL CENTER LAYOUT**

1"=1'-0"

A  
E04



**TYPICAL VFD PANEL LAYOUT**

NOT TO SCALE

MCC CONTROL DEVICES	
MCC SECTION	NAMEPLATE SCHEDULE
1A	SURGE PROTECTION DEVICE (SPD)
1D	POWER MONITOR
1G	MCC MAIN DISCONNECT
2A	ACTIVE HARMONIC FILTER FEEDER
2D	PANEL "L"
2H	LIGHTING TRANSFORMER AND DISCONNECT
3A	PUMP 1 ELAPSED TIME (HOURS) START COUNTS EMERGENCY STOP PUMP RUNNING PUMP FAULT PUMP HAND-OFF-AUTO PUMP OVERTEMP ALARM PUMP SEAL FAIL ALARM EMERGENCY STOP PUMP OVERTEMP ALARM RESET
4A	PUMP 2 ELAPSED TIME (HOURS) START COUNTS EMERGENCY STOP PUMP RUNNING PUMP FAULT PUMP HAND-OFF-AUTO PUMP OVERTEMP ALARM PUMP SEAL FAIL ALARM EMERGENCY STOP PUMP OVERTEMP ALARM RESET
5A	PUMP 3 ELAPSED TIME (HOURS) START COUNTS EMERGENCY STOP PUMP RUNNING PUMP FAULT PUMP HAND-OFF-AUTO PUMP OVERTEMP ALARM PUMP SEAL FAIL ALARM EMERGENCY STOP PUMP OVERTEMP ALARM RESET
6A	PUMP 4 ELAPSED TIME (HOURS) START COUNTS EMERGENCY STOP PUMP RUNNING PUMP FAULT PUMP HAND-OFF-AUTO PUMP OVERTEMP ALARM PUMP SEAL FAIL ALARM EMERGENCY STOP PUMP OVERTEMP ALARM RESET
7A	ACTIVE HARMONIC FILTER


**CALL 48 HOURS BEFORE YOU DIG**  
1-800-424-5555 (811)  
UNDERGROUND SERVICE



**MOTOR CONTROL CENTER DETAILS**


NO.	DATE	DESCRIPTION	BY	REVIEW
1	03/27/19	ISSUED FOR BIDDING	OMP	RJF





**DIAGRAM 1: PUMP, TYP.**

NO SCALE



**DIAGRAM 2: BACKUP FLOAT CONTROL LOGIC**

NO SCALE

**CALL 48 HOURS BEFORE YOU DIG**  
**1-800-424-5555 (811)**  
 UNDERGROUND SERVICE



SIGNED: 03/27/19



SIGNED: 03/27/19

CITY OF LYNNWOOD  
 LIFT STATION 8  
 IMPROVEMENTS



**CONTROL LOGIC DIAGRAMS**


NO.	DATE	DESCRIPTION	BY	REVIEW
03/27/19		ISSUED FOR BIDDING		



CALL 48 HOURS  
BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE



SIGNED: 03/27/19



SIGNED: 03/27/19


CITY OF LYNNWOOD  
LIFT STATION 8  
IMPROVEMENTS





**GENERATOR DETAILS**

NO.	DATE	DESCRIPTION	BY	REVIEW
1	03/27/19	ISSUED FOR BIDDING	OMP	RUF


ENGINEER: RMS	DATE: Mar 25, 2019	CLIENT: LYNN	JOB NO.: 117288
REVIEWED: CMR	PLOT DATE: Mar 26, 2019	FILENAME: LSRD-ELEC08.DWG	
SCALE: SHOWN DRAWING IS FULL SCALE WHEN BAR MEASURES 2"			
DWG NO.: E08	SHEET NO.: 35	48	



**GENERATOR AND FUEL TANK PLAN VIEW**  
1/2" = 1'-0"



**BOLLARD DETAIL**  
NOT TO SCALE




**GENERATOR AND FUEL TANK SIDE ELEVATION VIEW**  
1/2" = 1'-0"











**TYPICAL ELECTRICAL TRENCH DETAIL**

NOT TO SCALE  
 NOTE: BURY DEPTH OF CONDUIT AND HORIZONTAL SPACING SHALL BE CONFIRMED WITH SERVING UTILITY BEFORE CONSTRUCTION.




**PROPOSED CHECK VALVE LIMIT SWITCH DETAIL**  
 NOT TO SCALE



**CARD READER DETAIL**  
 NOT TO SCALE

ELECTRICAL NOTES	
XXX	1. SEE DWG NO. E12 FOR CONDUIT AND CONDUCTOR SCHEDULE.



**OUTDOOR SITE LIGHT AND SECURITY CAMERA DETAIL**  
 NOT TO SCALE

CALL 48 HOURS BEFORE YOU DIG  
 1-800-424-5555 (811)  
 UNDERGROUND SERVICE

**RH2 ENGINEERING**  
 40 YEARS SINCE 1978  
 BOTHELL, WA  
 22722 29th Drive SE, Suite 210  
 www.rh2.com 1.800.720.8052



SIGNED: 03/27/19



SIGNED: 03/27/19

CITY OF LYNNWOOD  
 LIFT STATION 8 IMPROVEMENTS



**ELECTRICAL DETAILS I**



DATE	DESCRIPTION	BY	REVIEW
03/27/19	ISSUED FOR BIDDING	OMP	RJF

ENGINEER	DATE	REVISIONS
KMS	Mar 26, 2019	
CMR	Mar 26, 2019	


SCALE: SHOWN  
 DRAWING IS FULL SCALE WHEN BAR MEASURES 2"  
 DWG NO.: E10 SHEET NO.: 37/48




CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE




**WET WELL TRANSDUCER AND FLOAT SWITCH DETAIL**  
NOT TO SCALE




**GROUND TEE DETAIL**  
NOT TO SCALE




**GROUND REBAR DETAIL**  
NOT TO SCALE




**GROUND TEE DETAIL**  
NOT TO SCALE



**GROUND CROSS DETAIL**  
NOT TO SCALE



**FLOOD SWITCH DETAIL**  
NOT TO SCALE



**GROUND ROD DETAIL**  
NOT TO SCALE


NO.	DATE	DESCRIPTION	BY	REVIEW
1	03/27/19	ISSUED FOR BIDDING	OMP	RUF








CALL 48 HOURS BEFORE YOU DIG  
 1-800-424-5555 (811)  
 UNDERGROUND SERVICE




SIGNED: 03/27/19




SIGNED: 03/27/19



**TELEMETRY PANEL EXTERIOR LAYOUT**  
 NOT TO SCALE



**TELEMETRY PANEL INTERIOR SWING DOOR LAYOUT**  
 NOT TO SCALE




**FIBER OPTIC PANEL EXTERIOR LAYOUT**  
 NOT TO SCALE



CITY OF LYNNWOOD  
 LYNNWOOD WASHINGTON  
 LIFT STATION 8 IMPROVEMENTS  
 RTU - PANEL LAYOUT

ENGINEER	DATE	DESCRIPTION	NO.	DATE	BY	REVIEW
REVISIONS						
ISSUED FOR BIDDING	03/27/19					





**RTU POWER LAYOUT**  
NOT TO SCALE



**FIBER OPTIC PANEL POWER LAYOUT**  
NOT TO SCALE

CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE

**RH2 ENGINEERING**  
40 YEARS SINCE 1978  
BOTHELL, WA  
22722 29th Drive SE, Suite 210  
www.rh2.com 1.800.720.8052



SIGNED: 03/27/19



SIGNED: 03/27/19

CITY OF LYNNWOOD  
LIFT STATION 8  
IMPROVEMENTS





**RTU - POWER DIAGRAM**

ENGINEER	DATE	REVISIONS	NO.	DATE	DESCRIPTION
KMS	Mar 26, 2019	ISSUED FOR BIDDING	1		
CMR	Mar 26, 2019				


SCALE	SHOWN
0"	1"
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"	
DWG NO. E14	SHEET NO. 41
48	



COMPACTLOGIX 1769 PLC BASE,  
MODEL NO. 1769-L33ER




**RTU COMMUNICATIONS LAYOUT**  
NOT TO SCALE



**FIBER OPTIC PANEL COMMUNICATIONS LAYOUT**  
NOT TO SCALE

CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE

**RH2 ENGINEERING**  
40 YEARS SINCE 1978  
BOTHELL, WA  
22722 29th Drive SE, Suite 210  
www.rh2.com 1.800.720.8052



SIGNED: 03/27/19



SIGNED: 03/27/19

CITY OF LYNNWOOD  
LIFT STATION 8 IMPROVEMENTS  
LYNNWOOD WASHINGTON

**RTU - COMMUNICATIONS DIAGRAM**

ENGINEER	DATE	REVISION	DESCRIPTION	DATE	BY	REVIEW
KMS	03/27/19	1	ISSUED FOR BIDDING			
CMR						

SCALE: SHOWN

DRAWING IS FULL SCALE WHEN BAR MEASURES 2"

DWG NO. E15 SHEET NO. 42 OF 48



CALL 48 HOURS  
BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE

**RH2**  
ENGINEERING  
40 YEARS SINCE 1978  
BOTHELL, WA  
22722 29th Drive SE, Suite 210  
www.rh2.com 1.800.720.8052



SIGNED: 03/27/19




SIGNED: 03/27/19


CITY OF LYNNWOOD  
LIFT STATION 8  
IMPROVEMENTS



RTU - PLC INPUT & OUTPUT WIRING I



**DIGITAL INPUTS, SLOT 1**  
NOT TO SCALE




**DIGITAL INPUTS, SLOT 2**  
NOT TO SCALE

ENGINEER	DATE	REVISION	DESCRIPTION	DATE	BY	REVIEW
KMS	Mar 26, 2019	1	ISSUED FOR BIDDING			
CMR	Mar 26, 2019					




CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE

**RH2**  
ENGINEERING  
40 YEARS SINCE 1978  
BOTHELL, WA  
22722 29th Drive SE, Suite 210  
www.rh2.com 1.800.720.8052



**DIGITAL INPUTS, SLOT 3**  
NOT TO SCALE




**DIGITAL INPUTS, SLOT 4**  
NOT TO SCALE

CITY OF LYNNWOOD  
LIFT STATION 8  
IMPROVEMENTS  
LYNNWOOD  
WASHINGTON  
**RTU - PLC INPUT & OUTPUT WIRING II**

ENGINEER	DATE	REVISION	DESCRIPTION	DATE	BY	REVIEW
KMS	Mar 26, 2019	ISSUED FOR BIDDING				
CMR	Mar 26, 2019					



CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE




SIGNED: 03/27/19




SIGNED: 03/27/19

CITY OF LYNNWOOD  
LIFT STATION 8  
IMPROVEMENTS  
LYNNWOOD  
WASHINGTON


**RTU - PLC INPUT & OUTPUT WIRING III**



**DIGITAL INPUTS, SLOT 5**  
NOT TO SCALE




**DIGITAL OUTPUTS, SLOT 6**  
NOT TO SCALE




ENGINEER	DATE	REVISION	ISSUED FOR BIDDING	DATE	DESCRIPTION	NO.	DATE	BY	REVIEW
KMS	Mar 26, 2019	1	ISSUED FOR BIDDING	03/27/19					
CMR	Mar 26, 2019	2							







**ANALOG INPUTS, SLOT 7**  
NOT TO SCALE



**ANALOG OUTPUTS, SLOT 9**  
NOT TO SCALE




**ANALOG INPUTS, SLOT 8**  
NOT TO SCALE



**ANALOG OUTPUTS, SLOT 10**  
NOT TO SCALE

**CALL 48 HOURS BEFORE YOU DIG**  
1-800-424-5555 (811)  
UNDERGROUND SERVICE



**CITY OF LYNNWOOD**  
LIFT STATION 8 IMPROVEMENTS  
**RTU - PLC INPUT & OUTPUT WIRING IV**

ENGINEER	DATE	REVISION	DESCRIPTION	DATE	BY	REVIEW
KMS	Mar 26, 2019	ISSUED FOR BIDDING				
CMR	Mar 26, 2019					



CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE


BJRD LLC.  
PARCEL NO. 00372800300203  
(VANDERWALL PROPERTY)

**DEMOLITION NOTES**


- 1 SAWCUT EXISTING ASPHALT.
- 2 REMOVE APPROX. 249 SF OF ASPHALT TO SUBGRADE.
- 3 REMOVE AND PROPERLY DISPOSE OF TREE AND ROOT BALL. REMOVE ROOTS AND OTHER ORGANICS AS NECESSARY TO CONSTRUCT PROPOSED IMPROVEMENTS. (TYPICAL ALL TREES IDENTIFIED IN RED).
- 4 REMOVE EXISTING FORCEMAIN AS NECESSARY TO CONSTRUCT PROPOSED IMPROVEMENTS.
- 5 REMOVE THE EXISTING EMERGENCY GENERATOR AND CONCRETE PAD TO FACILITATE CONSTRUCTION OF THE PROPOSED GRAVITY MAIN. PROVIDE BACKUP PUMPING SYSTEM FOR ANY/ALL SCENARIOS WHERE IN THE EXISTING INFRASTRUCTURE DOES NOT HAVE FULL REDUNDANCY. VACTOR BYPASS OF THE LIFT STATION SHALL BE NECESSARY TO FACILITATE CORING OF THE EXISTING WET WELL AND/OR MAKING CONNECTIONS TO THE EXISTING SYSTEM.
- 6 REMOVE APPROX. 52 LF OF EXISTING FENCE AS NECESSARY TO CONSTRUCT PROPOSED IMPROVEMENTS.
- 7 TEMPORARILY REMOVE EXISTING GATE.
- 8 DO NOT DISTURB EXISTING WALL.
- 9 PROVIDE CONSTRUCTION ENTRANCE PER CITY STANDARD DETAIL STD2-9 ON THIS SHEET.
- 10 PROVIDE SILT FENCE PER CITY STANDARD DETAIL STD2-5 ON DWG NO. C11.
- 11 PROVIDE INLET PROTECTION PER DETAIL ON DWG NO. C11.

**NOTES**

- SITE ACCESS SHALL BE LIMITED TO THE EAST ACCESS ROAD AND NOT FROM THE VANDERWALL PROPERTY TO THE NORTH.



**EXISTING SITE PLAN**  
1" = 10'



**VICINITY MAP**  
1" = 400'




**EXISTING SITE PHOTO**




**EXISTING SITE PHOTO**

TEMPORARILY RELOCATE GENERATOR DURING THE CONSTRUCTION OF UNDERGROUND UTILITIES. CONTRACTOR TO PROVIDE TEMPORARY POWER FEED FROM THE RELOCATED GENERATOR TO THE EXISTING STATION.

TREES TO BE REMOVED PER THIS SHEET  
REMOVE FENCE TO THIS POST  
TEMPORARILY REMOVE GATE DURING CONSTRUCTION  
ELECTRICAL PANELS TO BE PROTECTED IN PLACE




**EXISTING SITE PHOTO**



- NOTES:**
- 1 QUARRY SPALLS 4" - 8"
  - 2 SEE FIGURE 4.2 IN THE CURRENT ADOPTED STORMWATER MANAGEMENT MANUAL FOR WESTERN WASHINGTON DETAILS. NOTE: THE MINIMUM 100LF OF ENTRANCE SHALL BE REDUCED TO THE MAXIMUM PRACTICABLE SIZE WHEN THEN SIZE OR CONFIGURATION OF THE SITE DOES NOT ALLOW THE FULL LENGTH (100LF).
  - 3 EXISTING DRIVEWAY RAMP, OR SITE ACCESS ROAD 20' WIDE MIN. MATERIAL MUST BE EQUAL TO OR BETTER THAN SPECIFIED IN NOTE 1.
  - 4 A SEPARATION GEOTEXTILE SHALL BE PLACED UNDER THE SPALLS TO PREVENT FINE SEDIMENT FROM PUMPING UP INTO THE ROCK PAD. THE GEOTEXTILE SHALL MEET THE FOLLOWING STANDARDS:  
GRAB TENSILE STRENGTH (ASTM D4751) 200 PSI MIN.  
GRAB TENSILE ELONGATION (ASTM D4632) 30% MAX.  
MULLEN BURST STRENGTH (ASTM D3786-80A) 400 PSI MIN.  
AOS (ASTM D4751) 20-45 (U.S. STANDARD SIEVE SIZE)


	TEMPORARY CONSTRUCTION ENTRANCE	DRAWING NUMBER	STD2-9
		SCALE	NONE
		REVISION DATE	03/17
		DEPARTMENT	PW



ENGINEER	OMP	DATE	Mar 26, 2019	JOB NO.	117-288
CLIENT	LYNN	FILENAME	LS4-PH-D-CV01.DWG	REVISIONS	
REVIEWED	RJF	ISSUED FOR BIDDING		DATE	
DATE		DESCRIPTION		BY	
NO.					




CALL 48 HOURS BEFORE YOU DIG  
1-800-424-5555 (811)  
UNDERGROUND SERVICE




**SEWER NOTES**


- TRENCH SECTION FOR SEWER GRAVITY AND FORCEMAIN SHALL BE PER CITY OF LYNNWOOD STANDARD DRAWING STD6-12 ON DWG NO. C10.
- ANY LANDSCAPED OR VEGETATED AREAS DISTURBED BY CONSTRUCTION ACTIVITIES SHALL BE RESTORED TO EXISTING OR BETTER CONDITION.
- ALL THRUST BLOCKING SHALL BE PER CITY STANDARD DRAWING STD 5-5 ON DWG NO. C12.




**SEWER MAIN PLAN**  
1" = 10'



**SEWER MAIN PROFILE**  
1" = 10', V: 1" = 10'



**CONNECTION DETAIL**  
NOT TO SCALE



**VICINITY MAP**  
1" = 400'

CITY OF LYNNWOOD  
LIFT STATION 4 AND 8 IMPROVEMENTS  
SCHEDULE A: LIFT STATION 4  
LYNNWOOD WASHINGTON  
LS4 SANITARY SEWER PLAN & PROFILE

ENGINEER	DATE	REVISION	DESCRIPTION	DATE	BY	REVIEW
OMP	03/27/19	ISSUED FOR BIDDING				
RJF						
OMP						

SCALE: SHOWN  
DRAWING IS FULL SCALE WHEN BAR MEASURES 2"  
DWG NO.: C101 STREET NO.: 48 48