



ALTERNATIVE WITH  
PLANTER STRIP



ALTERNATIVE WITHOUT  
PLANTER STRIP



LOCAL/LOCAL ACCESS  
INTERSECTION

NOTES:

1. CURB RAMPS SHOULD BE LOCATED:
  - 1.1. AS CLOSE AS POSSIBLE TO EACH OTHER (MIN. 12' ARC LENGTH) TO PROVIDE SIGHT DISTANCE FOR BOTH DRIVERS AND PEDESTRIANS.
  - 1.2. WITHIN CROSSWALKS, AS CLOSE AS POSSIBLE TO THE INTERSECTION TRAVELED WAY PER WSDOT DESIGN MANUAL 1510.10(1).
2. ALL INTERSECTIONS SHALL HAVE 2 CURB RAMPS AT EACH CORNER, UNLESS ALL OTHER DESIGN OPTIONS ARE UNABLE TO BE CONSTRUCTED DUE TO EXISTING SITE CONSTRAINTS.
3. IF CROSSWALKS ARE MARKED, RAMPS ARE TO BE CONTAINED WITHIN CROSS WALK MARKINGS; OTHERWISE, GRIND AND REPLACE CROSSWALK TO ALIGN WITH CURB RAMPS.

DRAWING NUMBER	ST-SID-2
SCALE	NONE
REVISION DATE	12/20
DEPARTMENT	PW