



#### NOTES:

1. APPLIES TO STREETSCAPE TYPE 3 CORE.
2. 1/4" MICROTUBING FOR FLOWER BASKETS IRRIGATION SHALL BE BLACK AND UV RESISTANT.
3. WATER EMITTERS FOR FLOWER BASKETS SHALL BE A 360 DEGREE MINI SPRAY EMITTER, CAPABLE OF OPERATING FROM 15 TO 45 PSI, RADIUS OF 18" @ 25PSI (EMITTING APPROX. 10.3 GPH), WITH FLOW ADJUSTMENT AND SHUT OFF OPTION. THE EMITTER SHALL BE SUITABLE FOR 1/4" MICRO TUBING, INSTALLED ON SPIKE. ALL MATERIALS SHALL BE UV STABILIZED. PROVIDE ONE EMITTER PER FLOWER BASKET.
4. FURNISH AND INSTALL TUBING FROM PAVEMENT OR PLANTING AREA VALVE BOX CONNECTION TO LUMINAIRE POLE AND UP TO ACCESS HOLE PROVIDED FOR MICROTUBING AT FLOWER BASKET ARMS. SPLIT SUPPLY LINE OUTSIDE POLE WITH 1/4" BARBED TEE TO SUPPLY MICROTUBING TO EACH HANGING BASKET. COIL 3' EXCESS (MIN.) MICROTUBING TO EACH BASKET LOCATION. TIE TUBING TO BASKET ARMS NEATLY WITH BLACK WIRE TIES OR OTHER APPROVED FASTENER.
5. FURNISH REQUIRED NUMBER OF DRIP EMITTERS AND SPIKES FOR FLOWER BASKETS.