



SIGN TYPE	A*	B	C	D	E	F	G
POST MOUNTED 25 & 30 MPH	30" MIN	8"	.5"	1.5"	1.5" MIN	4"	4"
MOUNTED 35 MPH	VAR	12"	.5"	2.5"	4" MIN	4"	6"
MOUNTED SR 99	VAR	14"	.5"	2.5"	5.3" MIN	6"	8"
OVERHEAD (SIGNAL MAST ARMS)	VAR	16"	.5"	3.5"	6" MIN	8"	12"

*VARIABLE LENGTHS REQUIRED FOR NAMED STREETS.

NOTES:

- THIS STANDARD DETAIL ONLY APPLIES OUTSIDE THE CITY CENTER. SEE CITY CENTER STANDARD DETAILS CC-SIGN-7, CC-SIGN-8, & CC-SIGN-9.
- MATERIALS:
 - SIGN SHALL BE .080 FLAT ALUMINUM WITH ENGINEER GRADE FLOURESCENT DIAMOND GRADE SHEETING.
 - POST MATERIAL PER WSDOT STD. G-24.50-05.
- COLOR SHALL BE GREEN BACKGROUND WITH WHITE LETTERS, NUMBERS AND BORDER.
- TEXT SHALL BE FHWA D SERIES FONT.
- ALL LETTERING SHALL BE COMPOSED OF A COMBINATION OF LOWER-CASE LETTERS WITH INITIAL UPPER-CASE LETTERS EXCEPT FOR GEOGRAPHIC DELINEATORS WHICH SHALL BE COMPOSED OF UPPER CASE LETTERS ONLY.
- NUMBERED STREET NAMES SHALL NOT USE THE ORDINAL FORM OF THE NUMBER SUCH AS 1ST, 2ND, 3RD, 4TH ETC.
- MOUNTING, PLACEMENT AND FOUNDATION AS REQUIRED PER APPROVED PLANS AND/OR WSDOT STD. G-25.10-05, G-20.10-02, AND G-24.50-05.
- ALL OVERHEAD MOUNTED (TRAFFIC SIGNAL MAST ARMS) SHALL BE PER PLANS OR WSDOT STD. G-30.10-04.