



#### NOTES:

1. ALL TYPE 2 CB'S EQUIPPED WITH OPEN GRATES SHALL BE LOCKING TYPE.
2. ALL TYPE 2 CB'S NOT IN PAVED AREAS SHALL BE EQUIPPED WITH LOCKING LIDS.
3. CB'S SHALL BE SET SO THAT STEPS ARE DIRECTLY UNDER OPENING.
4. ALL TYPE 2 CB'S SHALL BE EQUIPPED WITH STEPS AND LADDER PER WSDOT STANDARD PLAN B-30.90-02.
5. CONCRETE SHALL BE CLASS 4000.
6. MIN DISTANCE FROM INVERT TO CB BOTTOM SHALL BE 2.0'.
7. CB SECTIONS AND LID WILL BE HS20 TRAFFIC LOAD CERTIFIED BY MFG.
8. GROUT INSIDE AND OUTSIDE CB SECTIONS.
9. HOLE SIZE = PIPE OD + 5". MAX MAX HOLE SIZE = 36" (48" CB) MAX HOLE SIZE = 42" (54" CB)
10. PIPES SHALL NOT PENETRATE MORE THAN 3" BEYOND WALL AND PENETRATIONS SHALL BE MUDDIED INTO A SMOOTH ROUNDED CONDITION.
11. NON SLIP LID REQUIRED FOR MANHOLES WITHIN WALKING PATHS, TYP.

